

WARNING: Contains Acetone 67-64-1, Hexane isomers - various, Oil modified urethane - proprietary, Mineral spirits 8052-41-3, 1-methoxy-2-propanol acetate 108-65-6, n-hexane 110-54-3, and Liquid petroleum gas 68476-86-8. This product is extremely flammable and should be kept away from all sources of ignition. Do not puncture, incinerate, or store container above 120°F. Exposure to high temperature may cause bursting. Do not place in direct sunlight or other heat sources. Deliberate misuse by concentrating and inhaled the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while products is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Overexposure to vapor may cause irritation to the nose and throat and may also cause dizziness, drowsiness and other central nervous system effects. Inhalation of the mist may cause irritation to the respiratory tract and irregular heartbeats. **FIRST AID:** If exposed, wash eyes with warm water. If ingested may be harmful or fatal. DO NOT induce vomiting. For severe overexposure, call a physician immediately. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state, and federal regulations. For additional information, consult the MSDS for this product.

To view Emergency M.S.D.S.: Tear (DO NOT CUT) label by running fingernail between perforations. Fold back label. Do not remove until can is empty.

KEEP AWAY FROM CHILDREN

- DIRECTIONS:** Read entire label before using this product.
1. Do not apply while equipment is energized.
 2. Clean surface thoroughly with a CRC® Cleaner/Degreaser or Precision Cleaner.
 3. Mask area not to be sprayed.
 4. Best results are obtained when sprayed above 60°F. Spray from 12-15 inches away in light, even coats.
 5. Additional coats for heavy film can be applied when first coat is dry. For maximum adhesion, apply additional coats in less than 48 hours.
 6. Removal: use a CRC® Cleaner/Degreaser.
 7. When finished spraying, clean valve by turning can upside down and pressing button until only pressure escapes. If clogging occurs, remove button and clean slot and orifice with fine wire.

SPECIAL USAGE WARNINGS:

- Contents extremely flammable.
- Do not smoke while spraying.
- Extinguish all flames, pilot lights and heaters.
- Do not apply while equipment is energized.
- Vapors will accumulate readily and may ignite.
- Use only with adequate ventilation.
- Maintain ventilation during use and until all vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.



- INSULATES electrical and electronic equipment and components.
- RESISTS abrasion.
- SEALS OUT water and moisture.
- HIGH DI-ELECTRIC STRENGTH, high surface and volume resistivity.
- MAINTAINS electrical characteristics over a temperature range of -90°F to +250°F.
- MATERIAL SAFETY DATA SHEET printed on back of label for your convenience and safety. (The CRC® MSD/L™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).



08A
CRC#505B
Made in U.S.A.



Urethane® Seal Coat

- Electrical & Electronic Insulator
- Flexible, Non-Conductive Polyurethane Film

TECHNICAL DATA

Resin System: polyurethane
Dry Time: Heat — -90°F to +250°F
 Tack free — 15 to 30 minutes
 Fully dry — 72 hours
 Recoat — Within 48 Hours

Resistance:
 Heat — -90°F to +250°F
 Abrasion — good
 Oil — good

Clear 18411

Net Wt. 11 oz. (312g)



DANGER! EXTREMELY FLAMMABLE.
 HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE.
 READ WARNINGS ON BACK PANEL.

DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. CONTENTS UNDER PRESSURE.

©2008 CRC Industries, Inc.
 Warminster, PA 18974
 Part # 18411
 Net Wt. 11 oz. (312g)
 CRC#505B 08A
 www.crcindustries.com



Material Safety Data Label from CRC
U.S. Patent Number 5,056,827

CLEAR URETHANE SEAL COAT® AEROSOL

PRODUCT - 18411

- M5D18411

24 HOUR EMERGENCY INFORMATION - CALL CHEMTREC 1-800-424-9300

PHONE: (215) 674-4300

885 LOUIS DRIVE, WARMINTERS, PA 18974

MANUFACTURED BY: CRC INDUSTRIES, INC.

M.S.D.[.]TM



HAZARDOUS INGREDIENT INFORMATION

CAS #	ACGIH	OSHA	OTHER	%	SARA 313
8052413	100 ppm	NE	NE	10.20	No
propylal	100 ppm	NE	NE	10.20	No
1-methoxy-2-propanol	NE	NE	NE	2.6	No
acetone	500 ppm	NE	NE	15.25	No
Acetone isomers	500 ppm	NE	NE	1.2	Yes
n-Hexane	50 ppm	NE	NE	25.35	No
110543	1000 ppm	NE	NE	1.2	Yes
68476868	1000 ppm	NE	NE	25.35	No

CHEMICAL AND PHYSICAL PROPERTIES

Appearance and Odor: Clear viscous liquid, solvent odor.
 Specific Gravity: 0.8163
 Boiling Point: 120°F (initial)
 Freezing Point: ND
 Evaporation Rate: >1 (Butyl acetate=1)
 Vapor Density: Negligible (>1 air=1)
 Vapor Pressure: ND
 pH: NA
 %VOC: 63.9

FIRE AND EXPLOSION DATA

Flashpoint: <20°F
 Method: TCC
 LEL: 1.0
 UEL: 8.0
 Unusual Hazards: Aerosol containers may explode when heated above 120°F.
 Reactivity: Stable
 Hazardous Decomposition products: Thermal: Carbon monoxide, Carbon dioxide and various hydrocarbons.
 gaseous; strong acids or alkalis.

REACTIVITY AND STABILITY

PROTECTION INFORMATION

Ventilation: Maintain below TLV. Use mechanical means if necessary.
 Respiratory: Self contained breathing apparatus above TLV.
 Eye & Face: Safety goggles.
 Other Protective Equipment: Use a splash apron and boots if splashing occurs.

HAZARDS IDENTIFICATION

Signs and Symptoms of Exposure

1. Acute Overexposure:

INHALATION: Irritation of respiratory tract, headaches, dizziness, central nervous system depression. SKIN: Mild irritation. EYES: Direct contact with product causes irritation. High vapor concentrations may irritate eyes. INGESTION: Swallowing a large amount may be harmful. Absorption of this material into the lungs during swallowing or vomiting may result in chemical pneumonitis.

2. Chronic Overexposure:

Repeated or overexposure may cause harm to the central nervous system and may result in permanent brain damage.
 Medical Conditions Generally Aggravated by Exposure: Respiratory and skin conditions.

Chemical listed as Carcinogen or Potential Carcinogen
 OSHA: NO IARC Monographs: No NTP: No

EMERGENCY AND FIRST AID MEASURES

Inhalation:

Remove to fresh air. Apply artificial respiration if necessary.
 If symptoms persist, call a physician.

Eye Contact:

Flush with large amounts of water for at least 15 minutes.

Skin:

Wash exposed area thoroughly with soap and water.

Ingestion:

DO NOT induce vomiting. Call a physician.

ACCIDENTAL RELEASE MEASURES

Handling and Storage: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding.
 Steps to be taken in case material is released or spilled: Usually not a problem with aerosols. Ventilate area, remove sources of ignition, absorb liquid with inert material and place in a closed container.
 Waste Disposal: All used and unused product should be disposed of in conformance with local, state and federal regulations.

NFPA/HMIS HAZARD RATINGS

Health: 2 Flammability: 3 Reactivity: 0 PPE: B

ADDITIONAL INFORMATION

Prepared By: Michelle Rudnick
 Technical Information: (800) 521-3168
 This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate.
 Date 2/27/08
 CRC#5058
 ND=Not Determined
 PM=Parts Per Million
 TCC=Top Closed Cup
 UEL=Upper Exposure Limit
 PPE=Personal Protection Equipment
 RL=Reportable Quantity
 lbs./gal. pounds per gallon