



CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 5/8/2025 Version: 1.0

SECTION 1: Identification

1.1. Identification

Trade name : CRC® Gasket Remover, 12 Wt Oz
Product code : 1003638
Part number : 05021

1.2. Recommended use and restrictions on use

Recommended use : Gasket remover
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
United States
T 1-800-556-5074
crcindustries.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300
24-Hour Emergency

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1

Skin corrosion/irritation, Category 2

Serious eye damage/eye irritation, Category 2A

Carcinogenicity, Category 2

Reproductive toxicity, Category 1B

Specific target organ toxicity – Single exposure, Category 3, Narcosis

Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Specific target organ toxicity — Repeated exposure, Category 2

Hazardous to the aquatic environment — Acute Hazard, Category 3

Extremely flammable aerosol. Pressurized container: may burst if heated.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May cause respiratory irritation.

May cause damage to organs (central nervous system, kidneys) through prolonged or repeated exposure.

Harmful to aquatic life.

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Extremely flammable aerosol
Pressurized container: may burst if heated
Causes skin irritation

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Precautionary statements (GHS US)	<p>Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness Suspected of causing cancer. May damage fertility or the unborn child May cause damage to organs (central nervous system, kidneys) through prolonged or repeated exposure</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Do not breathe vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves, protective clothing, eye and face protection. Wash hands thoroughly after handling. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.</p>
-----------------------------------	---

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Acetone	acetone, propan-2-one, propanone	CAS-No.: 67-64-1	45 – 75

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Name	Chemical name / Synonyms	Product identifier	%
N-methyl-2-pyrrolidone	1-Methyl-2-pyrrolidinone	CAS-No.: 872-50-4	10 – 30
Petroleum gases, liquefied, sweetened	Petroleum gases, liquefied, sweetened	CAS-No.: 68476-86-8	10 – 30
xylene	Xylene	CAS-No.: 1330-20-7	1 – 5
ethylbenzene	ethylbenzene	CAS-No.: 100-41-4	0.1 – 1

Comments : Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.
Chronic symptoms	: May damage fertility or the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water fog. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
---------------------------	--

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Protection during firefighting	: Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.
Additional Regulatory Information	: This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Evacuate unnecessary personnel. Eliminate every possible source of ignition. Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe vapors, spray, mist.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect spillage.
Methods for cleaning up	: Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination. Notify authorities if product enters sewers or public waters.
Additional Regulatory Information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not use if spray button is missing or defective. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Exposure to high temperature may cause can to burst. Prevent the build-up of electrostatic charge. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with skin and eyes. Do not breathe vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
-------------------------------	---

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Level 3 Aerosol. Keep in fireproof place. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Xylene, mixed isomers (Dimethylbenzene)
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair; Hematologic eff; Ototoxicity (p-xylene). Notations: OTO (Ototoxicant) (p isomer); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA	435 mg/m ³ 100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
NIOSH REL 10h TWA	100 ppm
NIOSH REL STEL	150 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
ethylbenzene (100-41-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl benzene
ACGIH OEL TWA	20 ppm
Remark (ACGIH)	TLV® Basis: URT & Eye irr; Kidney eff; Ototoxicity; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	Ethyl benzene
BEI	0.15 g/g Kreatinin Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: End of shift - Notations: Ns

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

ethylbenzene (100-41-4)	
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl benzene
OSHA PEL TWA	435 mg/m ³
	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Ethyl benzene
NIOSH REL 10h TWA	100 ppm
NIOSH REL STEL	125 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetone
ACGIH OEL TWA	594 mg/m ³
	250 ppm
ACGIH OEL STEL	1187 mg/m ³
	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	Acetone
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL TWA	2400 mg/m ³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Acetone
NIOSH REL 10h TWA	250 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

N-methyl-2-pyrrolidone (872-50-4)	
USA - ACGIH - Biological Exposure Indices	
Local name	N-Methyl-2-pyrrolidone
BEI	100 mg/l Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025
Petroleum gases, liquefied, sweetened (68476-86-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Butane
ACGIH OEL STEL	1000 ppm (EX - Explosion hazard)
Remark (ACGIH)	TLV® Basis: CNS impair
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Propane
OSHA PEL TWA	1800 mg/m ³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Wear protective gloves such as: Butyl rubber

Eye protection:

Wear safety glasses with side shields (or goggles).

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Colorless
Odor	: Solvent
Odor threshold	: No data available
Melting point	: -139.6 °F (-95.4 °C) estimated
Freezing point	: -139.6 °F (-95.4 °C) estimated
Boiling point	: 132.8 °F (56 °C) estimated
Flammability (solid, gas)	: Not applicable.
Explosion limits	: No data available
Flash point	: -4 °F (-20 °C) estimated
Auto-ignition temperature	: 450 °F (232.33 °C) estimated
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Solubility	: Water: Soluble
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: No data available
Evaporation rate	: Fast
Density and/or relative density	
Density	: 7.09 lb/gal Concentrate
Relative density	: 0.85 Concentrate
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available
Explosive properties	: Pressurized container: may burst if heated.
Oxidizing properties	: No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.3. Possibility of hazardous reactions

May mass explode in fire. Heating may cause a fire or explosion.

10.4. Conditions to avoid

High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Acids. Strong oxidizing agents. Strong acids. Halogens. Peroxides. Phenols.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Symptoms/effects	: May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation.
Symptoms/effects after eye contact	: Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause mild irritation to the digestive tract.
Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	> 4200 mg/kg
LC50 Inhalation - Rat [ppm]	5922 ppm
LC50 Inhalation - Rat (Dust/Mist)	> 10000 mg/l
LC50 Inhalation - Rat (Vapors)	29 mg/l/4h

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg Source: ECHA, HSDB
LD50 dermal rabbit	> 20000 mg/kg Source: ECHA
LC50 Inhalation - Rat [ppm]	4000 ppm Source: ECHA, Harmonized classification of EU CLP
LC50 Inhalation - Rat (Dust/Mist)	17200 mg/l
LC50 Inhalation - Rat (Vapors)	18.96 mg/l/4h

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg Source: ECHA
LD50 dermal rabbit	> 7400 mg/kg Source: ECHA
LC50 Inhalation - Rat (Dust/Mist)	50100 mg/l
LC50 Inhalation - Rat (Vapors)	76 mg/l Source: ECHA

N-methyl-2-pyrrolidone (872-50-4)	
LD50 oral rat	4150 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 5.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 5.1 mg/l Source: ECHA
LC50 Inhalation - Rat (Vapors)	> 5.1 mg/l/4h

Petroleum gases, liquefied, sweetened (68476-86-8)	
LC50 Inhalation - Rat (Dust/Mist)	658 mg/l Source: IUCLID

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Carcinogenicity : Suspected of causing cancer.

xylene (1330-20-7)	
IARC group	3 - Not classifiable
ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
N-methyl-2-pyrrolidone (872-50-4)	
NOAEL (chronic,oral,animal/male,2 years)	≈ 89 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity)
NOAEL (chronic,oral,animal/female,2 years)	≈ 221 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: OECD Guideline 451 (Carcinogenicity Studies), Guideline: EU Method B.32 (Carcinogenicity Test), Guideline: EPA OTS 798.3300 (Carcinogenicity)

Reproductive toxicity : May damage fertility or the unborn child.

Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg body weight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg body weight Animal: rat, Animal sex: male
N-methyl-2-pyrrolidone (872-50-4)	
LOAEL (animal/female, F0/P)	500 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
NOAEL (animal/male, F0/P)	≥ 500 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
NOAEL (animal/female, F0/P)	350 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
N-methyl-2-pyrrolidone (872-50-4)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs (central nervous system, kidneys) through prolonged or repeated exposure.

xylene (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bw/day
NOAEC (inhalation, rat, gas, 90 days)	> 810 ppm
ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
Acetone (67-64-1)	
NOAEL (oral, rat, 90 days)	900 mg/kg bw/day

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

N-methyl-2-pyrrolidone (872-50-4)	
LOAEL (dermal, rat/rabbit, 90 days)	1653 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 28 days)	820 mg/kg bw/day
NOAEL (dermal, rat/rabbit, 28 days)	< 413 mg/kg bw/day
NOAEC (inhalation, rat, 28 days)	0.1 mg/l
NOAEL (oral, rat, 90 days)	169 mg/kg bw/day
NOAEL (dermal, rat/rabbit, 90 days)	826 mg/kg body weight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEC (inhalation, rat, 90 days)	0.5 mg/l

Petroleum gases, liquefied, sweetened (68476-86-8)	
LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)
Viscosity, kinematic : No data available

xylene (1330-20-7)	
Viscosity, kinematic	0.86 mm ² /s

ethylbenzene (100-41-4)	
Viscosity, kinematic	0.641 mm ² /s

N-methyl-2-pyrrolidone (872-50-4)	
Viscosity, kinematic	1615.759 mm ² /s

Chronic symptoms : May damage fertility or the unborn child.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life.

xylene (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Source: ECHA
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 - Other aquatic organisms [1]	350 mg/l waterflea
EC50 - Other aquatic organisms [2]	3.9 mg/l
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l

ethylbenzene (100-41-4)	
LC50 - Fish [1]	5.1 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	2.2 mg/l waterflea
EC50 72h - Algae [1]	5.4 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

ethylbenzene (100-41-4)	
EC50 72h - Algae [2]	4.9 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [1]	2.6 mg/l Source: ECHA
EC50 96h - Algae [2]	7.7 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
Acetone (67-64-1)	
LC50 - Fish [1]	5540 mg/l Source: ECHA
EC50 - Crustacea [1]	12600 – 12700 mg/l
EC50 - Other aquatic organisms [1]	12600 mg/l waterflea
EC50 - Other aquatic organisms [2]	3400 mg/l
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
N-methyl-2-pyrrolidone (872-50-4)	
LC50 - Fish [1]	> 500 mg/l
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea
EC50 72h - Algae [1]	> 500 mg/l
EC50 72h - Algae [2]	672.8 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	25 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	12.5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
12.2. Persistence and degradability	
CRC® Gasket Remover, 12 Wt Oz	
Persistence and degradability	No data is available on the degradability of this product.
12.3. Bioaccumulative potential	
xylene (1330-20-7)	
BCF - Fish [1]	< 25.9 l/kg
Partition coefficient n-octanol/water (Log Pow)	3.16
ethylbenzene (100-41-4)	
BCF - Fish [1]	1 l/kg
Partition coefficient n-octanol/water (Log Pow)	3.15 Source: HSDB
Acetone (67-64-1)	
Partition coefficient n-octanol/water (Log Pow)	-0.24 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-0.23
N-methyl-2-pyrrolidone (872-50-4)	
BCF - Fish [1]	3.16 l/kg

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

N-methyl-2-pyrrolidone (872-50-4)	
Partition coefficient n-octanol/water (Log Pow)	-0.46
Petroleum gases, liquefied, sweetened (68476-86-8)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available




SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations	: Full or partially-full aerosol cans can be treated as universal waste. Empty container can be recycled.
Hazardous waste code	: Possible RCRA waste code includes: D001: Ignitable Waste
	However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.
Additional information	: Do not re-use empty containers. Contents under pressure.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
UN1950	1950	1950
14.2. Proper Shipping Name		
Aerosols (Limited quantity)	AEROSOLS (Limited quantity)	Aerosols, flammable (Limited quantity)
14.3. Transport hazard class(es)		
LTD QTY	LTD QTY	LTD QTY
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
No		

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

14.6. Special precautions for user

DOT

Class (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
UN-No. (DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

IMDG

Class (IMDG)	: 2.1 - Flammable gases
Special provision (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES
EmS-No. (Spillage)	: S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE)
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

IATA

Class (IATA)	: 2.1 - Gases : Flammable
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provision (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Toxic Substances Control Act (TSCA)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Name	CAS-No.	Commercial status	Flags
------	---------	-------------------	-------

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

xylene	1330-20-7	Active	
ethylbenzene	100-41-4	Active	
Acetone	67-64-1	Active	
N-methyl-2-pyrrolidone	872-50-4	Active	
Petroleum gases, liquefied, sweetened	68476-86-8	Active	
Propane	74-98-6	Active	
Butane	106-97-8	Active	
Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S			
N-methyl-2-pyrrolidone	CAS-No. 872-50-4	10 – 30%	

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

xylene (1330-20-7)	Listed on EPA Hazardous Air Pollutant (HAPS)
ethylbenzene (100-41-4)	Listed on EPA Hazardous Air Pollutant (HAPS)

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substance

CERCLA Section 103 (40CFR302.4)	Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.
---------------------------------	---

CERCLA RQ	
xylene (1330-20-7)	100 lb
ethylbenzene (100-41-4)	1000 lb
Acetone (67-64-1)	5000 lb

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 302 Extremely Hazardous Substance

Not listed

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Section 304 Emergency Release Notification

Not listed

Sections 311/312 Hazard Classification

CRC® Gasket Remover, 12 Wt Oz	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids)

Section 313 (TRI Reporting)

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

xylene	CAS-No.1330-20-7	1 – 5%
ethylbenzene	CAS-No.100-41-4	0.1 – 1%
N-methyl-2-pyrrolidone	CAS-No.872-50-4	10 – 30%

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65



WARNING:

This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer, and N-Methylpyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

U.S. - California - Proposition 65 - Carcinogens List	
Ethylbenzene(100-41-4)	XLISTED
Benzene(71-43-2)	XLISTED
Cumene(98-82-8)	XLISTED
Acetaldehyde(75-07-0)	XLISTED

U.S. - California - Proposition 65 - Reproductive Toxicity - Male	
Benzene(71-43-2)	XLISTED

U.S. - California - Proposition 65 - Developmental Toxicity	
Benzene(71-43-2)	XLISTED
Toluene(108-88-3)	XLISTED

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

U.S. - California - Proposition 65 - Developmental Toxicity	
Methanol(67-56-1)	XLISTED
N-Methylpyrrolidone(872-50-4)	XLISTED

State Regulations

Component	State Regulations
xylene(1330-20-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
ethylbenzene(100-41-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Acetone(67-64-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Rhode Island - Hazardous Substance List
N-methyl-2-pyrrolidone(872-50-4)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Propane(74-98-6)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List
Butane(106-97-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List

15.4 Other Regulatory Information

Volatile organic compound (VOC) regulation

EPA

VOC content (40 CFR 51.100(s))	47.5 %
Consumer products (40 CFR 59, Subpt. C))	Not regulated.

State

Consumer products	This product is regulated as a Gasket Adhesive Remover, Graffiti Remover and Paint Remover or Stripper. This product is compliant for use in all 50 states.
VOC Content (CA)	47.5 %
VOC Content (OTC)	47.5 %

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Author : Joshua Weir
Other information : CRC # 1002570.

Safety Data Sheet (SDS), USA, CRC

CRC® Gasket Remover, 12 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Inc.