



CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 2/5/2025 Version: 1.0

SECTION 1: Identification

1.1. Identification

Trade name : CRC® Wire Dryer, 6 Wt Oz
Product code : 1003722
Part number : 05104

1.2. Recommended use and restrictions on use

Recommended use : Wire dryer
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
United States
T 1-800-556-5074
crcindustries.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300
24-Hour Emergency

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Aerosol, Category 1

Extremely flammable aerosol. Pressurized container: may burst if heated.

Skin sensitization, Category 1

May cause an allergic skin reaction.

Aspiration hazard, Category 1

May be fatal if swallowed and enters airways.

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Extremely flammable aerosol
Pressurized container: may burst if heated
May be fatal if swallowed and enters airways
May cause an allergic skin reaction

Precautionary statements (GHS US)

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not apply while equipment is energized.
Extinguish all flames, pilot lights, and heaters.
Vapors will accumulate readily and may ignite.

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Avoid breathing vapors, spray, mist.
Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.
Wear protective gloves.
Contaminated work clothing must not be allowed out of the workplace.
If swallowed: Immediately call a poison center or doctor.
Do NOT induce vomiting.
If on skin: Wash with plenty of water.
If skin irritation or rash occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
Exposure to high temperature may cause can to burst.
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Chemical name / Synonyms | Product identifier | % |
|---|---|----------------------|---------|
| Distillates (petroleum), hydrotreated light | Distillates (petroleum), hydrotreated light | CAS-No.: 64742-47-8 | 60 – 80 |
| Carbon dioxide | Carbon dioxide | CAS-No.: 124-38-9 | 1 – 5 |
| Vanilla fragrances | Vanilla fragrances | CAS-No.: Proprietary | 0.1 – 1 |

Comments : Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact : Wash skin with soap and water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution. Get medical advice/attention if you feel unwell.

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

First-aid measures after ingestion : Call a physician immediately. Do not use mouth-to-mouth method if victim ingested the substance. Do not induce vomiting. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Prolonged inhalation may be harmful.
Symptoms/effects after skin contact : May cause an allergic skin reaction.
Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion : Aspiration may cause pulmonary edema and pneumonitis.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Alcohol resistant foam. Water fog. Dry powder. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurized container may rupture when exposed to heat or flame.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing vapors, spray, mist.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak, if possible without risk. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Exposure to high temperature may cause can to burst. Avoid contact with skin and eyes. Avoid breathing vapors, spray, mist. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product usage instructions, see the product label.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Level 3 Aerosol. Store locked up. Store in a cool, dry place out of direct sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
- Packaging materials : Store always product in container of same material as original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Carbon dioxide (124-38-9) | |
|--|------------------------|
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Carbon dioxide |
| ACGIH OEL TWA | 5000 ppm |
| ACGIH OEL STEL | 30000 ppm |
| Remark (ACGIH) | TLV® Basis: Asphyxia |
| Regulatory reference | ACGIH 2024 |
| USA - OSHA - Occupational Exposure Limits | |
| Local name | Carbon dioxide |
| OSHA PEL TWA | 9000 mg/m ³ |

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| Carbon dioxide (124-38-9) | |
|---|---|
| | 5000 ppm |
| Regulatory reference (US-OSHA) | OSHA Annotated Table Z-1 |
| USA - NIOSH - Occupational Exposure Limits | |
| Local name | Carbon dioxide |
| NIOSH REL 10h TWA | 5000 ppm |
| NIOSH REL STEL | 30000 ppm |
| Regulatory reference (US-NIOSH) | OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG)) |

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear protective gloves such as: Nitrile. Neoprene.

Eye protection:

Wear safety glasses with side shields (or goggles).

Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Blue-green
Odor : Vanilla
Odor threshold : No data available
Melting point : -72.4 °F (-58 °C) estimated
Freezing point : -72.4 °F (-58 °C) estimated
Boiling point : 212 °F (100 °C) estimated
Flammability (solid, gas) : Extremely flammable aerosol.
Explosion limits : Lower explosion limit: 0.6 % estimated
Upper explosion limit: 5.5 % estimated
Flash point : 187 °F (86.1 °C) Setofflash
Auto-ignition temperature : 456.8 °F (236 °C) estimated
Decomposition temperature : No data available
pH : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Solubility : No data available
Partition coefficient n-octanol/water (Log Pow) : No data available
Vapor pressure : 1811.3 hPa estimated

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|---------------------------------|---|
| Evaporation rate | : No data available |
| Density and/or relative density | |
| Density | : 6.82 lb/gal Concentrate |
| Relative density | : 0.82 Concentrate |
| Relative vapor density at 20°C | : > 1 (air=1) |
| Particle characteristics | : No data available |
| Explosive properties | : Pressurized container: may burst if heated. |
| Oxidizing properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurized container: may burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid temperatures exceeding the flash point. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-------------------------------------|---|
| Symptoms/effects after inhalation | : Prolonged inhalation may be harmful. |
| Symptoms/effects after skin contact | : May cause an allergic skin reaction. |
| Symptoms/effects after eye contact | : Direct contact with the eyes is likely to be irritating. |
| Symptoms/effects after ingestion | : Aspiration may cause pulmonary edema and pneumonitis. |
| Acute toxicity (oral) | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (dermal) | : Not classified (Based on available data, the classification criteria are not met) |
| Acute toxicity (inhalation) | : Not classified (Based on available data, the classification criteria are not met) |

Distillates (petroleum), hydrotreated light (64742-47-8)

| | |
|-----------------------------------|------------------------------|
| LD50 oral rat | > 15000 mg/kg Source: IUCLID |
| LD50 dermal rabbit | > 2000 mg/kg Source: IUCLID |
| LC50 Inhalation - Rat (Dust/Mist) | > 5.2 mg/l Source: IUCLID |

| | |
|-----------------------------------|--|
| Skin corrosion/irritation | : Not classified (Based on available data, the classification criteria are not met). |
| Serious eye damage/irritation | : Not classified (Based on available data, the classification criteria are not met) |
| Respiratory or skin sensitization | : May cause an allergic skin reaction. |

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|------------------------|---|
| Germ cell mutagenicity | : Not classified (Based on available data, the classification criteria are not met) |
| Carcinogenicity | : Not classified (Based on available data, the classification criteria are not met) |
| Reproductive toxicity | : Not classified (Based on available data, the classification criteria are not met) |

Distillates (petroleum), hydrotreated light (64742-47-8)

| | |
|---------------------------|--|
| NOAEL (animal/male, F0/P) | ≥ 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)] |
|---------------------------|--|

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Distillates (petroleum), hydrotreated light (64742-47-8)

| | |
|--------------------------|--|
| NOAEL (oral,rat,90 days) | 750 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) |
|--------------------------|--|

| | |
|-----------------------------------|---|
| NOAEL (dermal,rat/rabbit,90 days) | ≥ 495 mg/kg body weight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |
|-----------------------------------|---|

Aspiration hazard : May be fatal if swallowed and enters airways.

Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Carbon dioxide (124-38-9)

| | |
|-----------------|----------------------|
| LC50 - Fish [1] | 35 mg/l Source: HSDB |
|-----------------|----------------------|

Distillates (petroleum), hydrotreated light (64742-47-8)

| | |
|-----------------|-------------------------|
| LC50 - Fish [1] | 2.4 mg/l Source: ECOTOX |
|-----------------|-------------------------|

12.2. Persistence and degradability

CRC® Wire Dryer, 6 Wt Oz

| | |
|-------------------------------|--|
| Persistence and degradability | No data is available on the degradability of this product. |
|-------------------------------|--|

12.3. Bioaccumulative potential

Carbon dioxide (124-38-9)

| | |
|---|-------------------|
| Partition coefficient n-octanol/water (Log Pow) | 0.83 Source: ISCS |
|---|-------------------|

Distillates (petroleum), hydrotreated light (64742-47-8)

| | |
|---|------------------------|
| Partition coefficient n-octanol/water (Log Pow) | 3.3 – 6 Source: IUCLID |
|---|------------------------|

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 13: Disposal considerations




13.1. Disposal methods

| | |
|--|--|
| Regional waste regulation | : Dispose of contents/container in accordance with local/regional/national regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Sewage disposal recommendations | : Do not allow to enter sewers, surface or groundwater. |
| Product/Packaging disposal recommendations | : Full or partially-full aerosol cans can be treated as universal waste. Empty container can be recycled. Contents under pressure. |
| Hazardous waste code | : Possible RCRA waste code includes: D001: Ignitable Waste |

However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

| DOT | IMDG | IATA |
|---|---|---|
| 14.1. UN number | | |
| UN1950 | 1950 | 1950 |
| 14.2. Proper Shipping Name | | |
| Aerosols, flammable (Limited quantity) | AEROSOLS (Limited quantity) | Aerosols, flammable (Limited quantity) |
| 14.3. Transport hazard class(es) | | |
| LTD QTY | LTD QTY | LTD QTY |
|  |  |  |
| 14.4. Packing group | | |
| Not applicable | Not applicable | Not applicable |
| 14.5. Environmental hazards | | |
| No supplementary information available | | |

14.6. Special precautions for user

DOT

| | |
|--|--|
| Class (DOT) | : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115 |
| UN-No.(DOT) | : UN1950 |
| DOT Special Provisions (49 CFR 172.102) | : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols. |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 306 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 75 kg |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 150 kg |
| DOT Vessel Stowage Location | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel. |
| DOT Vessel Stowage Other | : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials |

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

IMDG

| | |
|-----------------------------|---|
| Class (IMDG) | : 2.1 - Flammable gases |
| Special provision (IMDG) | : 63, 190, 277, 327, 344, 381, 959 |
| Limited quantities (IMDG) | : SP277 |
| Excepted quantities (IMDG) | : E0 |
| Packing instructions (IMDG) | : P207, LP200 |
| Packing provisions (IMDG) | : PP87, L2 |
| EmS-No. (Fire) | : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES |
| EmS-No. (Spillage) | : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) |
| Stowage category (IMDG) | : None |
| Stowage and handling (IMDG) | : SW1, SW22 |
| Segregation (IMDG) | : SG69 |

IATA

| | |
|--|---------------------------|
| Class (IATA) | : 2.1 - Gases : Flammable |
| PCA Excepted quantities (IATA) | : E0 |
| PCA Limited quantities (IATA) | : Y203 |
| PCA limited quantity max net quantity (IATA) | : 30kgG |
| PCA packing instructions (IATA) | : 203 |
| PCA max net quantity (IATA) | : 75kg |
| CAO packing instructions (IATA) | : 203 |
| CAO max net quantity (IATA) | : 150kg |
| Special provision (IATA) | : A145, A167, A802 |
| ERG code (IATA) | : 10L |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Toxic Substances Control Act (TSCA)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

| Name | CAS-No. | Commercial status | Flags |
|---|-------------|-------------------|-------|
| Carbon dioxide | 124-38-9 | Active | |
| Distillates (petroleum), hydrotreated light | 64742-47-8 | Active | |
| Vanilla fragrances | Proprietary | Active | |

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substance

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

| | |
|---------------------------------|---|
| CERCLA Section 103 (40CFR302.4) | Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee. |
|---------------------------------|---|

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 302 Extremely Hazardous Substance

Not listed

Section 304 Emergency Release Notification

Not listed

Sections 311/312 Hazard Classification

Not listed

Section 313 (TRI Reporting)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

State Regulations

| Component | State Regulations |
|--|---|
| Carbon dioxide(124-38-9) | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Rhode Island - Hazardous Substance List |
| Distillates (petroleum), hydrotreated light(64742-47-8) | U.S. - Rhode Island - Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| Petrolatum(8009-03-8) | U.S. - Rhode Island - Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| Paraffin oils (petroleum), catalytic dewaxed heavy(64742-70-7) | U.S. - Massachusetts - Right To Know List |
| Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7) | U.S. - Rhode Island - Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List |
| Distillates (petroleum), hydrotreated light paraffinic(64742-55-8) | U.S. - Massachusetts - Right To Know List |
| Paraffin oils (petroleum), catalytic dewaxed light(64742-71-8) | U.S. - Massachusetts - Right To Know List |

CRC® Wire Dryer, 6 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

15.4 Other Regulatory Information

Volatile organic compound (VOC) regulation

EPA

| | |
|--|----------------|
| VOC content (40 CFR 51.100(s)) | 91.28 % |
| Consumer products (40 CFR 59, Subpt. C)) | Not regulated. |

State

| | |
|-------------------|----------------|
| Consumer products | Not regulated. |
| VOC Content (CA) | 0 % |
| VOC Content (OTC) | 0 % |

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Author : Joshua Weir
Other information : CRC # 510E/1002509.

Safety Data Sheet (SDS), USA, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Inc.