SAFETY DATA SHEET

1. Identification

Product identifier Sta-Lube Air Tool Oil - 1 gal

Other means of identification

Product Code No. SL2533 (Item# 1007837) Recommended use Lubricant for pneumatic equipment

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name

885 Louis Dr. **Address**

Warminster, PA 18974 US

Telephone 24-Hour Emergency

800-556-5074 800-424-9300 (US)

(CHEMTREC)

Website crcindustries.com

2. Hazard(s) identification

Not classified. **Physical hazards** Not classified. Health hazards **Environmental hazards** Not classified. **OSHA** defined hazards Not classified.

Label elements

Hazard symbol None. None. Signal word

The mixture does not meet the criteria for classification. **Hazard statement**

Precautionary statement

Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to Prevention

ensure a fresh air supply during use. Observe good industrial hygiene practices.

Response Wash hands after handling.

Store away from incompatible materials. Storage

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Petroleum distillates, hydrotreated heavy paraffinic		64742-54-7	45 - 50
Severely hydrotreated heavy naphthenic petroleum oil		64742-52-5	45 - 50

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical

attention if symptoms occur.

Remove and isolate contaminated clothing and shoes. Wash off with soap and plenty of water. Get Skin contact

medical attention if irritation develops and persists. Wash contaminated clothing before reuse.

Rinse immediately with plenty of water, also under the eyelids. Remove contact lenses, if present Eye contact

and easy to do. Get medical attention if irritation develops and persists.

Rinse mouth. Drink 1 or 2 glasses of water. Never give anything by mouth to a victim who is Ingestion

unconscious or is having convulsions. If ingestion of a large amount does occur, call a poison control center immediately. Do not induce vomiting without advice from poison control center.

Direct contact with eyes may cause temporary irritation.

Most important symptoms/effects, acute and delayed

Indication of immediate

Treat symptomatically. medical attention and special treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters Fire-fighting

equipment/instructions

Specific methods General fire hazards Use fire-extinguishing media appropriate for surrounding materials.

None known.

During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Cool containers exposed to heat with water spray and remove container, if no risk is involved. Use

Use standard firefighting procedures and consider the hazards of other involved materials.

standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. In case of spills, beware of slippery floors and surfaces. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up The product is immiscible with water and will spread on the water surface. Prevent entry into waterways, sewer, basements or confined areas.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. The product is insoluble in water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid the generation of oil mists. Wear appropriate personal protective equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Use appropriate container to avoid environmental contamination. Wash contaminated clothing before reuse. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Material name: Sta-Lube Air Tool Oil - 1 gal

No. SL2533 (Item# 1007837) Version #: 01 Issue date: 10-11-2023

Components	Туре	Value	
Petroleum distillates, hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	
	for Air Contaminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
Petroleum distillates, hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.
Severely hydrotreated heavy naphthenic petroleum oil (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
ACGIH			
Components	Туре	Value	Form
Petroleum distillates, hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction
US. ACGIH Threshold Limit			_
Components	Туре	Value	Form
Petroleum distillates, hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
Severely hydrotreated heavy naphthenic petroleum oil (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
U.S NIOSH			
Components	Туре	Value	Form
Petroleum distillates, hydrotreated heavy	STEL	10 mg/m3	Mist
parailinic (CAS 64742-54-7)			
paraminic (CAS 64742-54-7)	TWA	5 mg/m3	Mist
,			
paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Components		5 mg/m3 Value	Form
US. NIOSH: Pocket Guide to Components Petroleum distillates, hydrotreated heavy	o Chemical Hazards		
US. NIOSH: Pocket Guide to Components Petroleum distillates, hydrotreated heavy	o Chemical Hazards Type	Value	Form
US. NIOSH: Pocket Guide to Components Petroleum distillates, hydrotreated heavy paraffinic (CAS 64742-54-7) Severely hydrotreated heavy naphthenic petroleum oil (CAS	o Chemical Hazards Type STEL	Value 10 mg/m3	Form Mist.
US. NIOSH: Pocket Guide to	o Chemical Hazards Type STEL TWA	Value 10 mg/m3 5 mg/m3	Form Mist.

Biological limit values Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If product is heated above 70 °C (155 °F) in the presence of water, hydrogen sulfide vapors may be released. Ventilation should be sufficient to keep hydrogen sulfide levels below recommended exposure limits. Eye wash fountain is recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC).

Other Wear suitable protective clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Light amber.

Odor Mild petroleum.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

680 °F (360 °C) estimated

Flash point 396.0 °F (202.2 °C) Cleveland Open Cup

Evaporation rate Slow.

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Explosive limit - upper (%)

Not available.

Not available.

Vapor pressure Not available.

Vapor density >1 (air = 1)

Relative density 0.87

Solubility(ies)

Solubility (water) Insoluble.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperature Not available. **Viscosity** 21 - 25 cSt

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Decomposition of this product may yield oxides of boron, calcium, magnesium, nitrogen, phosphorus, sulfur including hydrogen sulfide and zinc as well as carbon monoxide, carbon

dioxide and/or low molecular weight hydrocarbons.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. **Eye contact** Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Product	Species	Test Results			
Sta-Lube Air Tool Oil - 1 gal					
<u>Acute</u>					
Dermal					
LD50	Rabbit	5100 mg/kg			
Inhalation					
LC50	Rat	2295 mg/m³, 4 hours			
Oral					
LD50	Rat	5097 mg/kg			
Components	Species	Test Results			

Petroleum distillates, hydrotreated heavy paraffinic (CAS 64742-54-7)

<u>Acute</u>

Dermal

LD50 Rabbit > 5000 mg/kg

Oral

LD50 Rat 5 g/kg

Severely hydrotreated heavy naphthenic petroleum oil (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

Vapor

LC50 Rat > 20 mg/l, 4 hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Serious eye damage/eye Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Petroleum distillates, hydrotreated heavy paraffinic

(CAS 64742-54-7)

3 Not classifiable as to carcinogenicity to humans.

Severely hydrotreated heavy naphthenic petroleum oil

3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-52-5)

Material name: Sta-Lube Air Tool Oil - 1 gal

No. SL2533 (Item# 1007837) Version #: 01 Issue date: 10-11-2023

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Further information This product has no known adverse effect on human health.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty **Disposal instructions**

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Not regulated. Hazardous waste code

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard **US federal regulations**

Communication Standard, 29 CFR 1910.1200.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Material name: Sta-Lube Air Tool Oil - 1 gal SDS US No. SL2533 (Item# 1007837) Version #: 01 Issue date: 10-11-2023

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil - unspecified (CAS 64742-52-5) Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified (CAS 64742-54-7)

US. New Jersey Worker and Community Right-to-Know Act

Not Listed.

US. Massachusetts RTK - Substance List

Oil mist (mineral) (CAS 64742-54-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Mineral oil mist (CAS 64742-54-7)

US. Rhode Island RTK

LUBRICATING OIL (MINERAL) (CAS 64742-54-7)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 0 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C) Not regulated

State

Consumer products Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 10-11-2023

Prepared by Angelina Cibulskis

Version # 01

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.