



Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)
Issue date: 10/9/2025 Version: 1.0

SECTION 1: Identification

1.1. Identification

Trade name : Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz
Product code : 1007942
Part number : SL35905

1.2. Recommended use and restrictions on use

Recommended use : Anti-seize and lubricating compound
Restrictions on use : None known

1.3. Supplier

Manufactured or sold by:

CRC Industries, Inc.
885 Louis Dr.
Warminster, PA 18974
United States
T 1-800-556-5074
crcindustries.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300
24-Hour Emergency

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Precautionary statements (GHS US) : Use only in well-ventilated areas.
Open doors and windows or use other means to ensure a fresh air supply during use.
Observe good industrial hygiene practices.
Wash hands after handling.
Store away from incompatible materials
Dispose of contents/container in accordance with local/regional/national regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
White mineral oil	White mineral oil (petroleum)	CAS-No.: 8042-47-5	30 - 40
Polyisobutylene	Polyisobutene, 2-Methyl-1-propene, Homopolymer	CAS-No.: 9003-27-4	20 - 30
Calcium carbonate	-	CAS-No.: 471-34-1	20 - 30
Talc (not containing asbestos fibers)	-	CAS-No.: 14807-96-6	10 - 20
Titanium oxide (TiO ₂)	-	CAS-No.: 13463-67-7	1 - 3
Amorphous fumed silica	Polydimethylsiloxane	CAS-No.: 112945-52-5	1 - 3
Amorphous silica	Silicon dioxide	CAS-No.: 7631-86-9	1 - 3
Fumed silica	-	CAS-No.: 68611-44-9	< 1

Comments : Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with soap and water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : None under normal conditions.
Symptoms/effects after skin contact : Repeated or prolonged contact may cause slight irritation to the skin.
Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Absorb spilled material with sand or earth.

Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Additional Regulatory Information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Wear personal protective equipment. For product usage instructions, see the product label.

Hygiene measures : Do not eat, drink or smoke when using this product. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Store in a cool, dry place out of direct sunlight.

Packaging materials : Store in original container.

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Amorphous fumed silica (112945-52-5)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	0.8 mg/m ³ 20 mppcf
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	6 mg/m ³
Talc (not containing asbestos fibers) (14807-96-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Talc
ACGIH® TLV® TWA	2 mg/m ³ (Containing no asbestos fibers. E - The value is for particulate matter containing no asbestos and < 1 % crystalline silica, R - Respirable particulate matter) 2 mg/m ³ (Containing asbestos fibers. R - Respirable particulate matter) 0.1 fibers/cm ³ (Containing asbestos fibers. F - Respirable fibers)
Remark (ACGIH)	Containing no asbestos fibers = TLV® Basis: Pulm fibrosis & func. Notations: A4 (Not classifiable as a Human Carcinogen) Containing asbestos fibers = TLV® Basis: Pneumoconiosis; Lung cancer; Mesothelioma. Notations: A1 (Confirmed Human Carcinogen)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))
OSHA PEL TWA	20 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - NIOSH - Occupational Exposure Limits	
Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))
NIOSH REL 10h TWA	2 mg/m ³ (Respirable fraction)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-3 Mineral Dusts (NIOSH Pocket Guide to Chemical Hazards (NPG))
White mineral oil (8042-47-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® STEL	10 mg/m ³
USA - OSHA - Occupational Exposure Limits	
OSHA PEL C	5 mg/m ³
Titanium oxide (TiO2) (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Titanium oxide (TiO₂) (13463-67-7)	
ACGIH® TLV® TWA	0.2 mg/m ³ (Nanoscale particles. R - Repirable particulate matter) 2.5 mg/m ³ (Finescale particles. R - Repirable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA	15 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
NIOSH REL 10h TWA	2.4 mg/m ³ (fine) 0.3 mg/m ³ (ultrafine)
Remark (NIOSH)	Ca = Potential occupational carcinogens (ultrafine particles)
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Amorphous silica (7631-86-9)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	0.8 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	6 mg/m ³
White mineral oil (petroleum) (8042-47-5)	
Occupational Exposure Limit	5 mg/mg ³ TLV (ACGIH)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Wear protective gloves such as: Nitrile
Eye protection:
Wear safety glasses with side shields (or goggles).
Skin and body protection:
Wear suitable protective clothing

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Respiratory protection:

Use a self-contained breathing apparatus for emergencies. No respiratory protection needed under normal use conditions. Air monitoring is needed to determine actual employee exposure levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Color	: Off-white
Odor	: Mild odor
Odor threshold	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flammability (solid, gas)	: Non flammable.
Explosion limits	: Not applicable
Flash point	: 445 °F (229.4 °C) Cleveland Open Cup Method
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
pH	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Vapor pressure	: < 0.01 kPa estimated
Evaporation rate	: Slow
Density and/or relative density	
Density	: 10.1 lb/gal
Relative density	: 1.21
Relative vapor density at 20°C	: No data available
Particle characteristics	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Additional Regulatory Information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat, sparks and flame.

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

10.5. Incompatible materials

Oxidizing agent. Acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Metal oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Repeated or prolonged contact may cause slight irritation to the skin.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: None under normal conditions.
Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Inhalation:dust,mist: Not classified (Based on available data, the classification criteria are not met).

Fumed silica (68611-44-9)

LD50 oral rat	> 5000 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal	> 2000 mg/kg body weight
LC50 Inhalation - Rat	≥ 0.477 mg/kg Source: International Uniform Chemical Information Database
LC50 Inhalation - Rat (Dust/Mist)	> 477 mg/l

Amorphous fumed silica (112945-52-5)

LD50 oral rat	> 3100 mg/kg Source: OECD Screening Information Data Set
---------------	--

Talc (not containing asbestos fibers) (14807-96-6)

LD50 oral rat	> 5000 mg/kg Source: ECHA
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)

White mineral oil (8042-47-5)

LD50 oral rat	> 5000 mg/kg Source: International Uniform Chemical Information Database
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Titanium oxide (TiO₂) (13463-67-7)

LD50 oral rat	> 5000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LD50 dermal	> 10000 mg/kg body weight
LC50 Inhalation - Rat (Dust/Mist)	> 6.82 mg/l Source: ECHA

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Calcium carbonate (471-34-1)	
LD50 oral	> 2000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Amorphous silica (7631-86-9)	
LD50 oral	> 5000 mg/kg body weight
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg Source: ECHA
LD50 dermal	> 2000 mg/kg body weight
LC50 Inhalation - Rat (Dust/Mist)	5.01 mg/l Source: ECHA
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)
Respiratory or skin sensitization	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met).
Amorphous silica (7631-86-9)	
NOAEL (chronic,oral,animal/male,2 years)	1800 – 3000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (chronic,oral,animal/female,2 years)	1800 – 3200 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met).
Talc (not containing asbestos fibers) (14807-96-6)	
NOAEL (oral,rat,90 days)	100 mg/kg body weight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
White mineral oil (8042-47-5)	
NOAEL (oral,rat,90 days)	≥ 1200 mg/kg body weight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Calcium carbonate (471-34-1)	
NOAEL (oral,rat,90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, 90 days)	0.399 mg/l
NOAEC (inhalation,rat,dust/mist/fume,90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Amorphous silica (7631-86-9)	
NOAEL (dermal,rat/rabbit,90 days)	≥ 10000 mg/kg body weight Animal: rabbit
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Viscosity, kinematic	: Not applicable

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Fumed silica (68611-44-9)	
LC50 - Fish [1]	> 10000 mg/l
EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 10000 mg/l
Talc (not containing asbestos fibers) (14807-96-6)	
LC50 - Fish [1]	89581.016 mg/l Source: ECHA
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Source: ECHA
NOEC (chronic)	1459.798 mg/l Test organisms (species): other: Duration: '30 d'
Polyisobutylene (9003-27-4)	
LC50 - Fish [1]	> 5600 mg/l Source: The ECOTOXicology database
White mineral oil (8042-47-5)	
LC50 - Fish [1]	> 10000 mg/l Source: IUCLID
Titanium oxide (TiO₂) (13463-67-7)	
LC50 - Fish [1]	> 100 mg/l
EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 10000 mg/l
EC50 72h - Algae [1]	> 50 mg/l Source: ECHA
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Calcium carbonate (471-34-1)	
LC50 - Fish [1]	> 56000 mg/l Source: ECOTOX
EC50 - Other aquatic organisms [1]	> 100 mg/l waterflea
EC50 72h - Algae [1]	> 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 96h - Algae [1]	22000 mg/l Source: Ecological Structure Activity Relationships
ErC50 algae	> 14 mg/l
Amorphous silica (7631-86-9)	
LC50 - Fish [1]	10000 mg/l Source: ECHA
EC50 - Crustacea [1]	> 5000 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	> 10000 mg/l waterflea
EC50 72h - Algae [1]	> 173.1 mg/l Source: ECHA
LOEC (chronic)	149.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

12.2. Persistence and degradability

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Persistence and degradability	No data is available on the degradability of this product.
-------------------------------	--

12.3. Bioaccumulative potential

Talc (not containing asbestos fibers) (14807-96-6)

Partition coefficient n-octanol/water (Log Pow)	-9.4 Source: ECHA
---	-------------------

White mineral oil (8042-47-5)

Partition coefficient n-octanol/water (Log Pow)	5.18 Source: Quantitative Structure Activity Relation
---	---

Calcium carbonate (471-34-1)

Partition coefficient n-octanol/water (Log Pow)	-2.12
---	-------

Amorphous silica (7631-86-9)

Partition coefficient n-octanol/water (Log Pow)	0.53
---	------

12.4. Mobility in soil

Calcium carbonate (471-34-1)

Mobility in soil	4.971 Source: Quantitative Structure Activity Relation
------------------	--

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation	: Dispose of contents/container in accordance with local/regional/national regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Do not allow to enter sewers, surface or groundwater.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Hazardous waste code	: This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.
Additional information	: Do not re-use empty containers.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
Not regulated.	Not regulated.	Not regulated.
14.2. Proper Shipping Name		
Not regulated.	Not regulated.	Not regulated.

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

DOT	IMDG	IATA
14.3. Transport hazard class(es)		
Not regulated.	Not regulated.	Not regulated.
14.4. Packing group		
Not regulated.	Not regulated.	Not regulated.
14.5. Environmental hazards		
No supplementary information available		

14.6. Special precautions for user

DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Toxic Substances Control Act (TSCA)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substance

Not listed

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 302 Extremely Hazardous Substance

Not listed

Section 304 Emergency Release Notification

Not listed

Sections 311/312 Hazard Classification

Not listed

Section 313 (TRI Reporting)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Sta-Lube® Food Grade Anti-Seize & Lubricating Compound, 8 Wt Oz

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

State Regulations

Component	State Regulations
Talc (not containing asbestos fibers)(14807-96-6)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Rhode Island - Hazardous Substance List
White mineral oil(8042-47-5)	U.S. - Rhode Island - Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Titanium oxide (TiO ₂)(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Rhode Island - Hazardous Substance List
Calcium carbonate(471-34-1)	U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Rhode Island - Hazardous Substance List; U.S. - New Jersey - Right to Know Hazardous Substance List
Amorphous silica(7631-86-9)	U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) List

15.4 Other Regulatory Information

Volatile organic compound (VOC) regulation

EPA

VOC content (40 CFR 51.100(s))	2.2 %
Consumer products (40 CFR 59, Subpt. C))	Not regulated.

State

Consumer products	Anti-seize lubricant. This product is compliant for use in all 50 states.
VOC Content (CA)	2.2 %
VOC Content (OTC)	2.2 %

SECTION 16: Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS)

Author : Angelina Cibulskis

Safety Data Sheet (SDS), USA, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Inc.