

SAFETY DATA SHEET

1. Identification

Product identifier Parts Cleaner & Degreaser - 1 lb 2 oz

Other means of identification

Item# 1751863 **Product Code**

Recommended use General purpose degreaser

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries, Inc. Company name

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

215-674-4300 **General Information** 800-521-3168 **Technical Assistance Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

> Gases under pressure Compressed gas Skin corrosion/irritation Category 2

Health hazards Serious eye damage/eye irritation Category 2A

Reproductive toxicity (fertility) Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin Hazard statement

irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or

dizziness. Suspected of damaging fertility.

Material name: Parts Cleaner & Degreaser - 1 lb 2 oz Item# 1751863 Version #: 01 Issue date: 02-22-2023

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapors. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.

Storage

Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

Disposal

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations.

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

3. Composition/information on ingredients

| | g | |
|----------|---|--|
| Mixtures | | |

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|-------------|---------|
| methyl acetate | | 79-20-9 | 45 - 55 |
| acetone | | 67-64-1 | 20 - 30 |
| carbon dioxide | | 124-38-9 | 5 - 10 |
| octamethylcyclotetrasiloxane | | 556-67-2 | 5 - 10 |
| naphtha (petroleum), hydrotreated light | | 64742-49-0 | 1 - 10 |
| heptane, branched, cyclic and linear | | 426260-76-6 | 1 - 3 |
| n-heptane | | 142-82-5 | 1 - 3 |
| isopropyl alcohol | | 67-63-0 | 0.1 - 1 |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and

delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| Components | Type | Value | |
|--|------|-------------|--|
| acetone (CAS 67-64-1) | PEL | 2400 mg/m3 | |
| | | 1000 ppm | |
| carbon dioxide (CAS 124-38-9) | PEL | 9000 mg/m3 | |
| | | 5000 ppm | |
| isopropyl alcohol (CAS 67-63-0) | PEL | 980 mg/m3 | |
| | | 400 ppm | |
| methyl acetate (CAS 79-20-9) | PEL | 610 mg/m3 | |
| | | 200 ppm | |
| naphtha (petroleum), hydrotreated light (CAS 64742-49-0) | PEL | 400 mg/m3 | |
| , and the second | | 100 ppm | |
| n-heptane (CAS 142-82-5) | PEL | 2000 mg/m3 | |
| | | 500 ppm | |
| US. ACGIH Threshold Limit Value | s | | |
| Components | Туре | Value | |
| acetone (CAS 67-64-1) | STEL | 500 ppm | |
| | TWA | 250 ppm | |
| carbon dioxide (CAS 124-38-9) | STEL | 30000 ppm | |
| | TWA | 5000 ppm | |
| isopropyl alcohol (CAS 67-63-0) | STEL | 400 ppm | |
| | TWA | 200 ppm | |
| methyl acetate (CAS 79-20-9) | STEL | 250 ppm | |
| | TWA | 200 ppm | |
| n-heptane (CAS 142-82-5) | STEL | 500 ppm | |
| | TWA | 400 ppm | |
| US. NIOSH: Pocket Guide to Cher | | | |
| Components | Туре | Value | |
| acetone (CAS 67-64-1) | TWA | 590 mg/m3 | |
| | | 250 ppm | |
| carbon dioxide (CAS 124-38-9) | STEL | 54000 mg/m3 | |
| | | 30000 ppm | |
| | TWA | 9000 mg/m3 | |
| | | 5000 ppm | |
| isopropyl alcohol (CAS 67-63-0) | STEL | 1225 mg/m3 | |
| | | 500 ppm | |
| | TWA | 980 mg/m3 | |
| | | 400 ppm | |

| US. NIOSH: Pocket Guide to Chem | ical Hazards | | |
|--|---------------------------|------------|--|
| Components | Туре | Value | |
| methyl acetate (CAS 79-20-9) | STEL | 760 mg/m3 | |
| | | 250 ppm | |
| | TWA | 610 mg/m3 | |
| | | 200 ppm | |
| naphtha (petroleum), hydrotreated light (CAS 64742-49-0) | TWA | 400 mg/m3 | |
| | | 100 ppm | |
| n-heptane (CAS 142-82-5) | Ceiling | 1800 mg/m3 | |
| | | 440 ppm | |
| | TWA | 350 mg/m3 | |
| | | 85 ppm | |
| US. Workplace Environmental Exp | osure Level (WEEL) Guides | | |
| Components | Туре | Value | |
| octamethylcyclotetrasiloxan e (CAS 556-67-2) | TWA | 10 ppm | |

Biological limit values

| ACGIH Biological Exposure Indices | ACGIH | Biological | Exposure | Indices |
|-----------------------------------|--------------|------------|----------|---------|
|-----------------------------------|--------------|------------|----------|---------|

| Components | Value | Determinant | Specimen | Sampling Time |
|------------------------------------|---------|-------------|----------|---------------|
| acetone (CAS 67-64-1) | 25 mg/l | Acetone | Urine | * |
| isopropyl alcohol (CAS 67-63-0) | 40 mg/l | Acetone | Urine | * |

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Aerosol.
Color Colorless.
Odor Mild solvent.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -144.4 °F (-98 °C) estimated Initial boiling point and boiling 132.4 °F (55.8 °C) estimated

range

-4.0 °F (-20.0 °C) estimated Flash point

Not available.

Fast. **Evaporation rate**

Flammability (solid, gas)

Upper/lower flammability or explosive limits 0.75 % estimated Explosive limit - lower (%) Explosive limit - upper (%) 16 % estimated

Vapor pressure 4518.1 hPa estimated

Vapor density > 2 (air = 1)0.86 estimated Relative density

Solubility(ies)

Slightly soluble. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

433 °F (222.8 °C) estimated **Auto-ignition temperature**

Not available. **Decomposition temperature Viscosity** Not available. 86.3 % estimated Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

Carbon oxides. Formaldehyde. Hydrocarbon fumes and smoke. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. May cause irritation to the

respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause

respiratory irritation. Skin irritation. May cause redness and pain.

Information on toxicological effects

Not known. **Acute toxicity**

Product **Species Test Results**

Parts Cleaner & Degreaser - 1 lb 2 oz

Acute Oral

ATEmix 34275 mg/kg bw

Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

May cause respiratory irritation. May cause drowsiness or dizziness.

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

acetone -0.24
isopropyl alcohol 0.05
methyl acetate 0.18
n-heptane 4.66
octamethylcyclotetrasiloxane 5.1

Bioconcentration factor (BCF)

naphtha (petroleum), hydrotreated light 10 - 2500 octamethylcyclotetrasiloxane Result: 12400

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This material and its container must be disposed of as hazardous waste. Full or partially-full

aerosol cans can be treated as universal waste. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Empty container can be recycled. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance

with all applicable regulations.

Hazardous waste code Possible RCRA waste code includes:

D001: Waste Flammable material with a flash point <140 F

F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent

However, it is the generator's responsibility to determine the proper classification and disposal

method at the time of disposal.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, Limited Quantity

Material name: Parts Cleaner & Degreaser - 1 lb 2 oz Item# 1751863 Version #: 01 Issue date: 02-22-2023 Transport hazard class(es)

2.1 Class Subsidiary risk 2.1 Label(s)

Packing group Not assigned.

Environmental hazards

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82 Packaging exceptions 306 304 Packaging non bulk Packaging bulk None

IATA

UN number UN1950

Aerosols, flammable, Limited Quantity **UN** proper shipping name

Transport hazard class(es)

2.1 **Class** Subsidiary risk

Not assigned. Packing group

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN1950 **UN** number

AEROSOLS, Limited Quantity **UN proper shipping name**

Transport hazard class(es)

2.1 **Class** Subsidiary risk

Not assigned. Packing group


Environmental hazards

Marine pollutant Yes, but exempt from the regulations.

EmS F-D. S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

CERCLA Hazardous Substance List (40 CFR 302.4)

acetone (CAS 67-64-1) methyl acetate (CAS 79-20-9)

CERCLA Hazardous Substances: Reportable quantity

acetone (CAS 67-64-1) 5000 LBS methyl acetate (CAS 79-20-9) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

octamethylcyclotetrasiloxane (CAS 556-67-2) 1.0 % One-Time Export Notification only.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

6532

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

acetone (CAS 67-64-1)

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6533

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

acetone (CAS 67-64-1)
Isopropyl alcohol (CAS 67-63-0)
Low priority
methyl acetate (CAS 79-20-9)
Low priority

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

categories

Gas under pressure Skin corrosion or irritation

Serious eye damage or eye irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

acetone (CAS 67-64-1)

isopropyl alcohol (CAS 67-63-0)

```
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
n-heptane (CAS 142-82-5)
octamethylcyclotetrasiloxane (CAS 556-67-2)
```

US. New Jersey Worker and Community Right-to-Know Act

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

US. Massachusetts RTK - Substance List

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

US. Pennsylvania Worker and Community Right-to-Know Law

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

US. Rhode Island RTK

acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) isopropyl alcohol (CAS 67-63-0) methyl acetate (CAS 79-20-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5)

California Proposition 65



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 benzene (CAS 71-43-2) Listed: February 27, 1987 cumene (CAS 98-82-8) Listed: April 6, 2010 ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 lead (CAS 7439-92-1) Listed: October 1, 1992 naphthalene (CAS 91-20-3) Listed: April 19, 2002

California Proposition 65 - CRT: Listed date/Developmental toxin

Listed: December 26, 1997 benzene (CAS 71-43-2) lead (CAS 7439-92-1) Listed: February 27, 1987 methanol (CAS 67-56-1) Listed: March 16, 2012 toluene (CAS 108-88-3) Listed: January 1, 1991

California Proposition 65 - CRT: Listed date/Female reproductive toxin

lead (CAS 7439-92-1) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

benzene (CAS 71-43-2) Listed: December 26, 1997 lead (CAS 7439-92-1) Listed: February 27, 1987 n-hexane (CAS 110-54-3) Listed: December 15, 2017

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR 9.5 %

51.100(s))

Consumer products Not regulated

(40 CFR 59, Subpt. C)

State

Consumer products This product is regulated as a General Purpose Degreaser (aerosol). This product is compliant for

use in all 50 states.

VOC content (CA) 9.5 % 9.5 % VOC content (OTC)

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name Australia Australian Inventory of Industrial Chemicals (AICIS) No Canada Yes Domestic Substances List (DSL) Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) No European Inventory of Existing Commercial Chemical Europe No

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan No Yes Korea Existing Chemicals List (ECL) New Zealand New Zealand Inventory No **Philippines** Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

02-22-2023 Issue date Prepared by Allison Yoon

Version # 01

Further information CRC # 1753978

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).