



# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Issue date: 10/16/2024 Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Trade name : Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz  
Product code : 1755904  
Part number : 007100

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Protects nozzles and surfaces  
Restrictions on use : None known

#### 1.3. Supplier

##### Manufactured or sold by:

CRC Industries, Inc.  
885 Louis Dr.  
Warminster, PA 18974  
United States  
T 1-800-556-5074  
[crcindustries.com](http://crcindustries.com)

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300  
24-Hour Emergency

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

|  |  |
|--|--|
| Aerosol, Category 3  | Pressurized container: may burst if heated.        |
| Skin corrosion/irritation Category 2   | Causes skin irritation.                            |
| Serious eye damage/eye irritation Category 2A  | Causes serious eye irritation.                     |
| Specific target organ toxicity – Single exposure, Category 3, Narcosis                     | May cause drowsiness or dizziness.                 |
| Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation | May cause respiratory irritation.                  |
| Aspiration hazard Category 1   | May be fatal if swallowed and enters airways.      |
| Hazardous to the aquatic environment – Acute Hazard Category 3                             | Harmful to aquatic life.                           |
| Hazardous to the aquatic environment – Chronic Hazard Category 3                           | Harmful to aquatic life with long lasting effects. |

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Pressurized container: may burst if heated  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye irritation  
May cause respiratory irritation  
May cause drowsiness or dizziness

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Avoid breathing vapors, spray, mist. Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves, eye protection, face protection. Wash hands thoroughly after handling. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst. Dispose of contents/container in accordance with local/regional/national regulations.

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : When exposed to extreme heat or hot surfaces, vapors may decompose to toxic gases such as hydrogen fluoride, hydrogen chloride, and possibly phosgene.

### 2.4. Unknown acute toxicity (GHS US)

No additional information available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name   | Chemical name / Synonyms                               | Product identifier | %       |
|--|--|--------------------|---------|
| Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)- | Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)- | CAS-No.: 406-78-0  | 30 – 60 |
| Ethene, 1,2-dichloro-, (1E)-                           | trans-dichloroethylene                                 | CAS-No.: 156-60-5  | 30 – 60 |
| Carbon dioxide   | Carbon dioxide   | CAS-No.: 124-38-9  | 1 – 5   |

Comments : Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                                       |  |
|---------------------------------------|--|
| First-aid measures after inhalation   | : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.   |
| First-aid measures after skin contact | : Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing.   |
| First-aid measures after eye contact  | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| First-aid measures after ingestion    | : Rinse mouth. Do not induce vomiting. Call a physician immediately.   |

### 4.2. Most important symptoms and effects (acute and delayed)

|                                     |   |
|-------------------------------------|---|
| Symptoms/effects                    | : May cause drowsiness or dizziness.  |
| Symptoms/effects after inhalation   | : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. May cause respiratory irritation. |
| Symptoms/effects after skin contact | : Causes skin irritation.   |
| Symptoms/effects after eye contact  | : Causes eye irritation.  |
| Symptoms/effects after ingestion    | : Risk of lung edema.   |

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

|                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | : Water spray. Dry powder. Foam. Carbon dioxide. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.               |

### 5.2. Specific hazards arising from the chemical

|  |  |
|--|--|
| Fire hazard                                      | : No fire hazard.  |
| Explosion hazard                                 | : Pressurized container may rupture when exposed to heat or flame.   |
| Reactivity in case of fire                       | : When exposed to extreme heat or hot surfaces, vapors may decompose to toxic gases such as hydrogen fluoride, hydrogen chloride, and possibly phosgene. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released.   |

### 5.3. Special protective equipment and precautions for fire-fighters

|                                |   |
|--------------------------------|---|
| Firefighting instructions      | : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.              |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |   |
|------------------|---|
| General measures | : Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters. |
|------------------|---|

#### 6.1.1. For non-emergency personnel

|                      |  |
|----------------------|--|
| Protective equipment | : Wear recommended personal protective equipment.  |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing vapors, spray, mist. Avoid contact with skin and eyes. |

#### 6.1.2. For emergency responders

|                      |   |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so.   |

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk. Collect spillage.
- Methods for cleaning up : Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Exposure to high temperature may cause can to burst. Avoid contact with skin and eyes. Avoid breathing vapors, spray, mist. Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear personal protective equipment. For product usage instructions, see the product label.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep in a cool, well-ventilated place away from heat.
- Storage conditions : Level 1 Aerosol. Store locked up. Store in a well-ventilated place. Store in a cool, dry place out of direct sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
- Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Carbon dioxide (124-38-9)                 |                          |
|---|--------------------------|
| USA - OSHA - Occupational Exposure Limits |                          |
| Local name                                | Carbon dioxide           |
| OSHA PEL TWA                              | 9000 mg/m <sup>3</sup>   |
|   | 5000 ppm                 |
| Regulatory reference (US-OSHA)            | OSHA Annotated Table Z-1 |

### 8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.3. Individual protection measures/Personal protective equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Hand protection:

Wear protective gloves such as: Nitrile. Fluoroelastomer (FKM)

#### Eye protection:

Safety glasses with side shields

#### Respiratory protection:

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |                            |
|---|----------------------------|
| Physical state                                  | : Liquid                   |
| Color   | : Colorless                |
| Odor  | : Solvent                  |
| Odor threshold                                  | : No data available        |
| Melting point                                   | : No data available        |
| Freezing point                                  | : No data available        |
| Boiling point                                   | : 120.56 °F estimated      |
| Flammability (solid, gas)                       | : No data available        |
| Explosion limits                                | : No data available        |
| Flash point                                     | : None (Setaflash)         |
| Auto-ignition temperature                       | : 860 °F estimated         |
| Decomposition temperature                       | : No data available        |
| pH  | : No data available        |
| Viscosity, kinematic                            | : No data available        |
| Viscosity, dynamic                              | : No data available        |
| Solubility                                      | : No data available        |
| Partition coefficient n-octanol/water (Log Pow) | : No data available        |
| Vapor pressure                                  | : No data available        |
| Density and/or relative density                 |                            |
| Density   | : 10.96 lb/gal Concentrate |
| Relative density                                | : 1.32 Concentrate         |
| Particle characteristics                        | : No data available        |
| Relative evaporation rate (butyl acetate=1)     | : No data available        |
| Relative vapor density at 20°C                  | : No data available        |
| Explosive properties                            | : No data available        |
| Oxidizing properties                            | : No data available        |

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Pressurized container: may burst if heated.

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

When exposed to extreme heat or hot surfaces, vapors may decompose to toxic gases such as hydrogen fluoride, hydrogen chloride, and possibly phosgene.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat.

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Carbonyl halogenides. Hydrogen chloride. Hydrogen fluoride. Phosgene.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

|                                     |   |
|-------------------------------------|---|
| Symptoms/effects                    | : May cause drowsiness or dizziness.  |
| Symptoms/effects after inhalation   | : Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. May cause respiratory irritation. |
| Symptoms/effects after skin contact | : Causes skin irritation.   |
| Symptoms/effects after eye contact  | : Causes eye irritation.  |
| Symptoms/effects after ingestion    | : Risk of lung edema.   |
| Acute toxicity (oral)               | : Not classified (Based on available data, the classification criteria are not met).  |
| Acute toxicity (dermal)             | : Not classified (Based on available data, the classification criteria are not met)   |
| Acute toxicity (inhalation)         | : Not classified (Based on available data, the classification criteria are not met)   |

#### Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)- (406-78-0)

|                       |   |
|-----------------------|---|
| LD50 oral rat         | > 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)   |
| LD50 dermal rat       | > 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity), Guideline: other: |
| LC50 Inhalation - Rat | > 24.61879 mg/l air Animal: rat, Animal sex: male, Guideline: other:  |

#### Ethene, 1,2-dichloro-, (1E)- (156-60-5)

|                    |                           |
|--------------------|---------------------------|
| LD50 oral rat      | 9939 mg/kg Source: ECHA   |
| LD50 dermal rabbit | > 5000 mg/kg Source: ECHA |

Skin corrosion/irritation : Causes skin irritation.

#### Carbon dioxide (124-38-9)

|    |                  |
|----|------------------|
| pH | 3.2 Source: HSDB |
|----|------------------|

Serious eye damage/irritation : Causes serious eye irritation.

#### Carbon dioxide (124-38-9)

|    |                  |
|----|------------------|
| pH | 3.2 Source: HSDB |
|----|------------------|

Respiratory or skin sensitization : Not classified (Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)  
STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

### Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)- (406-78-0)

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

### Ethene, 1,2-dichloro-, (1E)- (156-60-5)

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

### Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)- (406-78-0)

LOAEC (inhalation, rat, vapor, 90 days) : 16.358 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

NOAEL (oral, rat, 90 days) : 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

NOAEC (inhalation, rat, vapor, 90 days) : 12.2685 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.  
Viscosity, kinematic : No data available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

### Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)- (406-78-0)

LC50 - Fish [1] : > 76 mg/l Test organisms (species): Cyprinus carpio

EC50 72h - Algae [1] : > 24 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

EC50 72h - Algae [2] : > 213 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

### Ethene, 1,2-dichloro-, (1E)- (156-60-5)

LC50 - Fish [1] : 135 mg/l Source: ECHA

EC50 - Crustacea [1] : 220 mg/l Source: ECHA

EC50 72h - Algae [1] : 36.36 mg/l Source: ECHA

### Carbon dioxide (124-38-9)

LC50 - Fish [1] : 35 mg/l Source: HSDB

### 12.2. Persistence and degradability

### Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

Persistence and degradability : No data is available on the degradability of this product.

### 12.3. Bioaccumulative potential

### Ethene, 1,2-dichloro-, (1E)- (156-60-5)

Partition coefficient n-octanol/water (Log Pow) : 2.09 Source: ChemIDplus

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Carbon dioxide (124-38-9)

Partition coefficient n-octanol/water (Log Pow) 0.83 Source: ICS

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available




## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations. Do not allow to enter sewers, surface or groundwater.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Hazardous waste code : This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33).  
  
However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.  
Additional information : Contents under pressure. Do not re-use empty containers.

## SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

| DOT   | IMDG  | IATA  |
|---|---|---|
| <b>14.1. UN number</b>  |   |   |
| UN1950  | 1950  | 1950  |
| <b>14.2. Proper Shipping Name</b>   |   |   |
| Aerosols, non-flammable (Limited quantity)  | AEROSOLS (Limited quantity)   | Aerosols, non-flammable (Limited quantity)  |
| <b>14.3. Transport hazard class(es)</b>   |   |   |
| LTD QTY   | LTD QTY   | LTD QTY Y   |
|  |  |  |
| <b>14.4. Packing group</b>  |   |   |
| Not applicable  | Not applicable  | Not applicable  |
| <b>14.5. Environmental hazards</b>  |   |   |
| No  |   |   |

### 14.6. Special precautions for user

DOT  
Class (DOT) : 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| UN-No.(DOT)  | : UN1950   |
| DOT Packaging Exceptions (49 CFR 173.xxx)                        | : 306  |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 75 kg  |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)     | : 150 kg   |
| DOT Vessel Stowage Location                                      | : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  |
| DOT Vessel Stowage Other   | : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials |

### IMDG

|                             |   |
|-----------------------------|---|
| Class (IMDG)                | : 2.2 - Non-flammable, non-toxic gases                                    |
| Special provision (IMDG)    | : 63, 190, 277, 327, 344, 381, 959  |
| Limited quantities (IMDG)   | : SP277   |
| Excepted quantities (IMDG)  | : E0  |
| Packing instructions (IMDG) | : P207, LP200   |
| Packing provisions (IMDG)   | : PP87, L2  |
| EmS-No. (Fire)              | : F-D - FIRE SCHEDULE Delta - FLAMMABLE GASES                             |
| EmS-No. (Spillage)          | : S-U - SPILLAGE SCHEDULE Uniform - GASES (FLAMMABLE, TOXIC OR CORROSIVE) |
| Stowage category (IMDG)     | : None  |
| Stowage and handling (IMDG) | : SW1, SW22   |
| Segregation (IMDG)          | : SG69  |

### IATA

|  |  |
|--|--|
| Class (IATA)                                 | : 2.2 - Gases : Non-flammable, Non-toxic |
| PCA Excepted quantities (IATA)               | : E0                                     |
| PCA Limited quantities (IATA)                | : Y203                                   |
| PCA limited quantity max net quantity (IATA) | : 30kgG                                  |
| PCA packing instructions (IATA)              | : 203                                    |
| PCA max net quantity (IATA)                  | : 75kg                                   |
| CAO packing instructions (IATA)              | : 203                                    |
| CAO max net quantity (IATA)                  | : 150kg                                  |
| Special provision (IATA)                     | : A98, A145, A167, A802                  |
| ERG code (IATA)                              | : 2L                                     |

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Toxic Substances Control Act (TSCA)

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

| Name   | CAS-No.  | Commercial status | Flags |
|--|----------|-------------------|-------|
| Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)- | 406-78-0 | Active            | PMN;S |
| Ethene, 1,2-dichloro-, (1E)-                           | 156-60-5 | Active            | T     |

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |                  |          |  |
|---|------------------|----------|--|
| Carbon dioxide  | 124-38-9         | Active   |  |
| <b>Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S</b> |                  |          |  |
| Ethane, 1,1,2,2-tetrafluoro-1-(2,2,2-trifluoroethoxy)-  | CAS-No. 406-78-0 | 30 – 60% |  |
| Ethene, 1,2-dichloro-, (1E)-  | CAS-No. 156-60-5 | 30 – 60% |  |

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not listed

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substance

|                                 |   |
|---------------------------------|---|
| CERCLA Section 103 (40CFR302.4) | Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee. |
|---------------------------------|---|

### CERCLA RQ

|   |         |
|---|---------|
| Ethene, 1,2-dichloro-, (1E)- (156-60-5) | 1000 lb |
|---|---------|

### Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 302 Extremely Hazardous Substance

Not listed

### Section 304 Emergency Release Notification

Not listed

### Sections 311/312 Hazard Classification

Not listed

### Section 313 (TRI Reporting)

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

## 15.2. International regulations

No additional information available

## 15.3. US State regulations

### California Proposition 65

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## State Regulations

# Weld-Aid® Non-Flammable Anti-Spatter, 14 Wt Oz

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Component                              | State Regulations   |
|--|---|
| Ethene, 1,2-dichloro-, (1E)-(156-60-5) | U.S. - Massachusetts - Right To Know List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List   |
| Carbon dioxide(124-38-9)               | U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York City - Right to Know Hazardous Substances List; U.S. - Pennsylvania - RTK (Right to Know) List |

### 15.4 Other Regulatory Information

#### Volatile organic compound (VOC) regulation

##### EPA

|  |                |
|--|----------------|
| VOC content (40 CFR 51.100(s))           | 43.7 %         |
| Consumer products (40 CFR 59, Subpt. C)) | Not regulated. |

##### State

|                   |                |
|-------------------|----------------|
| Consumer products | Not regulated. |
| VOC Content (CA)  | 96 %           |
| VOC Content (OTC) | 43.7 %         |

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Author : Joshua Weir  
Other information : CRC # 1755905.

Safety Data Sheet (SDS), USA, CRC

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries Inc.