

# SAFETY DATA SHEET

### 1. Identification

Product identifier	Screwloose® Super Penetrant - 11 oz	
Other means of identification		
Product Code	No. 03060 (Item# 1003322)	
Recommended use	General purpose penetrant	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Manufactured or sold by:		
Company name	CRC Industries, Inc.	
Address	885 Louis Dr.	
	Warminster, PA 18974 US	
Telephone		
General Information	215-674-4300	
Technical Assistance	800-521-3168	
Customer Service	800-272-4620	
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)	
Website	www.crcindustries.com	
2. Hazard(s) identificatior	1	
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
lealth hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 4
OSHA defined hazards	Not classified.	
Label elements		
		>
Signal word	Danger	
Hazard statement	Extremely flammable aerosol. Contains gas ur swallowed and enters airways. Causes skin irr drowsiness or dizziness.	nder pressure; may explode if heated. May be fatal itation. Causes serious eye irritation. May cause
Precautionary statement		
Prevention	flame or other ignition source. Pressurized cor not apply while equipment is energized. Exting accumulate readily and may ignite. Use only o	one. Open doors and windows or use other means

to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapors. Wash thoroughly after handling. Wear eye protection/face protection. Wear protective gloves.

Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.	
Storage	Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), hydrotreated light		64742-47-8	70 - 80
naphtha (petroleum), hydrotreated heavy		64742-48-9	10 - 20
paraffin oils (petroleum), catalytic dewaxed heavy		64742-70-7	3 - 5
carbon dioxide		124-38-9	1 - 3
distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	1 - 3
oleic acid		112-80-1	1 - 3
paraffin oils (petroleum), catalytic dewaxed light		64742-71-8	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes. Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. Pressurized container may rupture when exposed to heat or flame. Will burn if involved in a fire.	
Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.	
Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.	
Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.	
Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.	
Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).	

### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S OSHA Components	Туре	Value		
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	TWA	5 mg/m3		
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1	1000)		
Components	Туре	Value	Form	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3		
		5000 ppm		
distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	PEL	5 mg/m3	Mist.	

omponents	Туре	Value	Form
araffin oils (petroleum), atalytic dewaxed heavy CAS 64742-70-7)	PEL	5 mg/m3	Mist.
araffin oils (petroleum), atalytic dewaxed light CAS 64742-71-8)	PEL	5 mg/m3	Mist.
CGIH	_		_
components	Туре	Value	Form
istillates (petroleum), ydrotreated heavy araffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction
S. ACGIH Threshold Limit		N.L.	<b>F</b>
omponents	Туре	Value	Form
arbon dioxide (CAS 24-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
istillates (petroleum), ydrotreated heavy araffinic (CAS 64742-54-7)	TWA	5 mg/m3	Inhalable fraction.
araffin oils (petroleum), atalytic dewaxed heavy CAS 64742-70-7)	TWA	5 mg/m3	Inhalable fraction.
araffin oils (petroleum), atalytic dewaxed light CAS 64742-71-8)	TWA	5 mg/m3	Inhalable fraction.
.S NIOSH			
omponents	Туре	Value	Form
istillates (petroleum), ydrotreated heavy araffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist
, , , , , , , , , , , , , , , , , , ,	TWA	5 mg/m3	Mist
S. NIOSH: Pocket Guide to	Chemical Hazards		
omponents	Туре	Value	Form
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
istillates (petroleum), ydrotreated heavy araffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.
aranino (070 074742-04-1)	TWA	5 mg/m3	Mist.
istillates (petroleum),	TWA	100 mg/m3	
ydrotreated light (CÁS 4742-47-8)		-	
araffin oils (petroleum), atalytic dewaxed heavy CAS 64742-70-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
araffin oils (petroleum), atalytic dewaxed light CAS 64742-71-8)	STEL	10 mg/m3	Mist.
,			
	TWA	5 mg/m3	Mist.

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.	
Individual protection measures,	such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection		
Hand protection	Wear protective gloves such as: Nitrile. Neoprene.	
Other	Wear appropriate chemical resistant clothing.	
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

## 9. Physical and chemical properties

-	
Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Light amber.
Odor	Petroleum.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-121 °F (-85 °C) estimated
Initial boiling point and boiling range	300.2 °F (149 °C) estimated
Flash point	141.0 °F (60.6 °C) Setaflash
Evaporation rate	Slow.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	0.6 % estimated
Flammability limit - upper (%)	8.3 % estimated
Vapor pressure	Not available.
Vapor density	> 4 (air = 1)
Relative density	0.81 estimated
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	401 °F (205 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	77.3 % estimated
10. Stability and reactivity	/
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport

Reactivity Chemical stability The product is stable and non-reactive under normal conditions of use, storage and transport. Material is stable under normal conditions.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.	
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.	
Incompatible materials	Strong oxidizing agents.	
Hazardous decomposition products	Aldehydes. Carbon oxides. Nitrogen oxides (NOx). Potassium oxide. Sulfur oxides. Ketones. Organic acids.	

## 11. Toxicological information

Information on likely routes of exposure

information on likely routes of e	xposule		
Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.		
Skin contact	Causes skin irritation.		
Eye contact	Causes serious eye irritation.		
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.		
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Diarrhea. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.		
Information on toxicological effe	ects		
Acute toxicity	May be fatal if swallowed and	enters airways.	
Components	Species	Test Results	
distillates (petroleum), hydrotreate <u>Acute</u> Dermal LD50	d light (CAS 64742-47-8) Rabbit	> 2000 mg/kg	
Inhalation LC50	Rat	> 5 mg/l, 4 hours	
<b>Oral</b> LD50	Rat	> 5000 mg/kg	
paraffin oils (petroleum), catalytic	dewaxed heavy (CAS 64742-70	-7)	
Acute			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
<b>Oral</b> LD50	Rat	> 5000 mg/kg	
		> 5000 mg/kg	
Skin corrosion/irritation	Causes skin irritation. Causes serious eye irritation.		
Serious eye damage/eye irritation	Causes senous eye initation.		
Respiratory or skin sensitization	ı		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	Not classifiable as to carcinogenicity to humans.		
IARC Monographs. Overall	Evaluation of Carcinogenicity		
(CAS 64742-54-7)	distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) 3 Not classifiable as to carcinogenicity to humans.		
naphtha (petroleum), hyd (CAS 64742-48-9)	-	3 Not classifiable as to carcinogenicity to humans.	
paraffin oils (petroleum), (CAS 64742-71-8)		3 Not classifiable as to carcinogenicity to humans.	
Not listed.	d Substances (29 CFR 1910.1	001-1055)	
NUL IISICU.			

US. National Toxicology Pro Not listed.	ogram (NTP) Report on Carcinogens	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological informatio	n	
Ecotoxicity	Toxic to aquatic life. May cause long lasting harmful effects to aquatic life.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential	No data available.	
Partition coefficient n-octar oleic acid	nol / water (log Kow) 7.64	
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	
13. Disposal consideratio	ons	
Disposal instructions	If discarded, this product is considered a RCRA ignitable waste, D001. Empty container can be	

Disposal instructions	If discarded, this product is considered a RCRA ignitable waste, D001. Empty container can be recycled. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

DOT


DO		
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable, Limited Quantity
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	-
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Special provisions	N82
	Packaging exceptions	306
	Packaging non bulk	None
	Packaging bulk	None
ΙΑΤ	Α	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable, Limited Quantity
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Packing group	-
	ERG Code	10L
	Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	
	Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	-
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special pressutions for us	ar Pood sofety instructions SDS and amorgonou pr

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



15. Regulatory informat	ion	
US federal regulations	This product is a "Hazard Standard, 29 CFR 1910.1	ous Chemical" as defined by the OSHA Hazard Communication 200.
TSCA Section 12(b) E	xport Notification (40 CFR 7	'07, Subpt. D)
Not regulated.		
SARA 304 Emergency	release notification	
Not regulated.		
OSHA Specifically Re	gulated Substances (29 CFF	R 1910.1001-1053)
Not listed.		
CERCLA Hazardous	Substance List (40 CFR 302.	4)
	m), hydrotreated light (CAS 6 Substances: Reportable qua	
distillates (petroleu (CAS 64742-47-8)	m), hydrotreated light	100 LBS
		nt at or above its RQ require immediate notification to the National Emergency Planning Committee.
Other federal regulations		
Clean Air Act (CAA) Secti	on 112 Hazardous Air Pollut	ants (HAPs) List
Not regulated.		
5	on 112(r) Accidental Release	e Prevention (40 CFR 68.130)
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Gas under pressure Skin corrosion or irritation
	Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure) Aspiration hazard

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

### SARA 313 (TRI reporting)

Not regulated.

#### US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)

#### US. New Jersey Worker and Community Right-to-Know Act carbon dioxide (CAS 124-38-9)

US. Massachusetts RTK - Substance List

carbon dioxide (CAS 124-38-9) distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)

#### US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9) distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9) oleic acid (CAS 112-80-1) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)

#### US. Rhode Island RTK

carbon dioxide (CAS 124-38-9) distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) distillates (petroleum), hydrotreated light (CAS 64742-47-8) oleic acid (CAS 112-80-1) paraffin oils (petroleum), catalytic dewaxed heavy (CAS 64742-70-7) paraffin oils (petroleum), catalytic dewaxed light (CAS 64742-71-8)

#### **California Proposition 65**

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov



California Proposition 65 - CRT: Listed date/0	Carcinogenic substance	
benzene (CAS 71-43-2)	Listed: February 27, 1987	
ethylbenzene (CAS 100-41-4)	Listed: June 11, 2004	
naphthalene (CAS 91-20-3)	Listed: April 19, 2002	
California Proposition 65 - CRT: Listed date/Developmental toxin		
benzene (CAS 71-43-2)	Listed: December 26, 1997	
toluene (CAS 108-88-3)	Listed: January 1, 1991	
California Proposition 65 - CRT: Listed date/Male reproductive toxin		
benzene (CAS 71-43-2)	Listed: December 26, 1997	

#### Volatile organic compounds (VOC) regulations

EPA		
VOC content (40 CFR 51.100(s))	97.2 %	
Consumer products (40 CFR 59, Subpt. C)	Not regulated	
State		
Consumer products	This product is regulated as a Penetrant. This product is compliant for	use in all 50 states.
VOC content (CA)	24.1 %	
VOC content (OTC)	24.1 %	
ernational Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

• • • •
10-08-2021
12-03-2021
Danica Fulmer
02
CRC # 575H/1002602
The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Composition / Information on Ingredients: Disclosure Overrides Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data