

SAFETY DATA SHEET

1. Identification

1. Identification						
Product identifier	Chlor-Free® Degreaser - 14 oz					
Other means of identification						
Product Code	No. 03185 (Item# 1003441)					
Recommended use	General purpose degreaser					
Recommended restrictions	None known.					
Manufacturer/Importer/Supplier/	/Distributor information					
Manufactured or sold by:						
Company name	CRC Industries, Inc.					
Address	885 Louis Dr.					
	Warminster, PA 18974 US					
Telephone						
General Information	215-674-4300					
Technical Assistance	800-521-3168					
Customer Service	800-272-4620					
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)					
Website	crcindustries.com					
2. Hazard(s) identification	I					
Physical hazards	Flammable aerosols	Category 1				
-	Gases under pressure	Compressed gas				
Health hazards	Skin corrosion/irritation	Category 2				
	Serious eye damage/eye irritation	Category 2A				
	Reproductive toxicity	Category 2				
	Specific target organ toxicity, single exposure	Category 3 narcotic effects				
	Aspiration hazard	Category 1				
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2				
	Hazardous to the aquatic environment, long-term hazard	Category 2				
OSHA defined hazards	Not classified.					
Label elements						
	$\land \land \land \land$					
		$\boldsymbol{>}$				
Signal word	Danger					
-						

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child.

Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

media

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	40 - 50
naphtha (petroleum), hydrotreated light		64742-49-0	40 - 50
carbon dioxide		124-38-9	5 - 10
n-hexane		110-54-3	0.1 - 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage,	Level 3 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Туре	Value	
acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	

Components		Туре			Value	
carbon dioxide (CAS 124-38-9)		PEL			9000 mg/m3	
					5000 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		PEL			400 mg/m3	
					100 ppm	
n-hexane (CAS 110-54-3)		PEL			1800 mg/m3	
					500 ppm	
US. ACGIH Threshold Lim	it Values					
Components		Туре			Value	
acetone (CAS 67-64-1)		STEL			500 ppm	
		TWA			250 ppm	
carbon dioxide (CAS 124-38-9)		STEL			30000 ppm	
		TWA			5000 ppm	
n-hexane (CAS 110-54-3)		TWA			50 ppm	
US. NIOSH: Pocket Guide	to Chemical H				Malua	
Components		Туре			Value	
acetone (CAS 67-64-1)		TWA			590 mg/m3	
		0751			250 ppm	
carbon dioxide (CAS 124-38-9)		STEL			54000 mg/m3	
		T \A/A			30000 ppm	
		TWA			9000 mg/m3 5000 ppm	
naphtha (petroleum), hydrotreated light (CAS		TWA			400 mg/m3	
64742-49-0)					100 ppm	
n-hexane (CAS 110-54-3)		TWA			180 mg/m3	
					50 ppm	
ogical limit values						
ACGIH Biological Exposu	re Indices					
Components	Value		Determinant	Specimen	Sampling Time	
acetone (CAS 67-64-1)	25 mg/l		Acetone	Urine	*	
n-hexane (CAS 110-54-3)	0.5 mg/l		2,5-Hexanedio ne, without hydrolysis	Urine	*	
* - For sampling details, plea	ase see the so	urce docu				
osure guidelines						
US - California OELs: Skir	designation					
n-hexane (CAS 110-54		. .		absorbed the	ough the skin.	
US ACGIH Threshold Limi	t Values: Skin	n designa	tion			

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Polyvinyl chloride (PVC). Viton/butyl.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance				
Physical state	Liquid.			
Form	Aerosol.			
Color	Colorless.			
Odor	Solvent.			
Odor threshold	Not available.			
рН	Not available.			
Melting point/freezing point	-139.6 °F (-95.4 °C) estimated			
Initial boiling point and boiling range	123.8 °F (51 °C) estimated			
Flash point	< 0 °F (< -17.8 °C) estimated			
Evaporation rate	Fast.			
Flammability (solid, gas)	Not available.			
Upper/lower flammability or expl	losive limits			
Explosive limit - lower (%)	1.2 % estimated			
Explosive limit - upper (%)	14.3 % estimated			
Vapor pressure	6825 hPa estimated			
Vapor density	> 1 (air = 1)			
Relative density	0.77 estimated			
Solubility(ies)				
Solubility (water)	Negligible.			
Partition coefficient (n-octanol/water)	Not available.			
Auto-ignition temperature	446 °F (230 °C) estimated			
Decomposition temperature	Not available.			
Viscosity	Not available.			
Percent volatile	92.5 %			

10. Stability and reactivity

Reactivity Chemical stability	The product is stable and non-reactive under normal conditions of use, storage and transport. Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.

Material name: Chlor-Free® Degreaser - 14 oz

No. 03185 (Item# 1003441) Version #: 04 Revision date: 04-04-2023 Issue date: 12-31-2019

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

toxicological characteristics redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.	
Components	Species Test Results	
n-hexane (CAS 110-54-3)		
Acute		
Dermal		
LD50	Rabbit	> 1300 mg/kg
Oral		150.10 //
LD50	Rat	15840 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall	Evaluation of Carcinogenicity	
Not listed.		
	ed Substances (29 CFR 1910.1001-1	053)
Not listed.	ogram (NTP) Report on Carcinogen	c
Not listed.	ogram (NTP) Report on Carcinogen	5
Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
	May be fatal if swallowed and enters airways.	
Aspiration hazard	5	

Ecotoxicity

Toxic to aquatic life with long lasting effects.


Components	Species	Test Results
n-hexane (CAS 110-54-3)		
Aquatic		
Acute		
Fish	LC50 Fathead minnov	w (Pimephales promelas) 2500 μg/l, 96 hours
Persistence and degradability	No data is available on the deg	gradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.	
Partition coefficient n-octane	ol / water (log Kow)	
acetone		-0.24
n-hexane Bioconcentration factor (BC	F)	3.9
naphtha (petroleum), hydrotrea	-	10 - 2500
n-hexane	5	501.187
Mobility in soil	No data available.	
Other adverse effects		al effects (e.g. ozone depletion, photochemical ozone creation
	potential, endocrine disruption,	, global warming potential) are expected from this component.
13. Disposal consideration	ns	
Disposal instructions	This material and its container	must be disposed of as hazardous waste. Full or partially-full
	aerosol cans can be treated as	s universal waste. Empty container can be recycled. Contents under
		aled containers. Dispose in accordance with all applicable
	regulations.	aludaa
Hazardous waste code	Possible RCRA waste code inc D001: Waste Flammable mater	
		Solvent - Spent Non-halogenated Solvent
	However, it is the generator's r	esponsibility to determine the proper classification and disposal
	method at the time of disposal.	
Contaminated packaging		
		retain product residue, follow label warnings even after container is
	emptied.	
14. Transport information		
DOT		
UN number	UN1950	
UN proper shipping name	Aerosols, flammable, Limited Quantity	
Transport hazard class(es)	2.4	
Class Subsidiary risk	2.1	
Subsidiary risk Label(s)	- 2.1	
Packing group	Not assigned.	
Environmental hazards	0	
Marine pollutant	No.	
	Read safety instructions, SDS and emergency procedures before handling.	
Special provisions	N82	
Packaging exceptions	306 Nor	
Packaging non bulk Packaging bulk	None None	
Other information		
Passenger and cargo	Allowed with restrictions.	
aircraft		
Cargo aircraft only	Allowed with restrictions.	

IA

Allowed with restrictions.
UN1950
Aerosols, flammable, Limited Quantity
2.1
-
Not assigned.
10L

Special precautions for user Other information	Read safety instructions, SDS and emergency procedures before handling.
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not assigned.
Environmental hazards	
Marine pollutant	Yes, but exempt from the regulations.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

acetone (CAS 67-64-1)

CERCLA Hazardous Substances: Reportable quantity

5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Toxic Substances Control Act (TSCA)

acetone (CAS 67-64-1)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-hexane (CAS 110-54-3)

Clean Air Act (CAA) Section Not regulated.	n 112(r) Accidental Rele	ase Prevention (40 C	CFR 68.130)	
Safe Drinking Water Act (SDWA)	Not regulated.			
Drug Enforcement Adn Chemical Code Numbe		2, Essential Chemica	lls (21 CFR 1310.02(b) and 13 [.]	10.04(f)(2) and
acetone (CAS 67-64 Drug Enforcement Adn		6532 I & 2 Exempt Chemi	cal Mixtures (21 CFR 1310.12((c))
acetone (CAS 67-64	l-1)	35 %WV		
acetone (CAS 67-64	Mixtures Code Number	6532		
			vor Manufacturing Workplace	9
acetone (CAS 67-64	,	Low priority		
Food and Drug Administration (FDA)	Not regulated.			
Superfund Amendments and Re	eauthorization Act of 19	86 (SARA)		
Classified hazard categories	Flammable (gases, ae Gas under pressure Skin corrosion or irritat Serious eye damage o Reproductive toxicity Specific target organ to Aspiration hazard Hazard not otherwise of	rosols, liquids, or solic ion r eye irritation oxicity (single or repea		
SARA 302 Extremely hazar Not listed.	dous substance			
SARA 311/312 Hazardous chemical	Yes			
SARA 313 (TRI reporting)				
Chemical name		CAS number 110-54-3	% by wt. 0.1 - 1	
US state regulations		110-34-3	0.1 - 1	
•	hemicals List. Safer Co	nsumer Products Re	egulations (Cal. Code Regs, ti	t. 22, 69502.3, subd.
acetone (CAS 67-64-1) naphtha (petroleum), hyd n-hexane (CAS 110-54-3 US. New Jersey Worker and		·		
acetone (CAS 67-64-1) carbon dioxide (CAS 124	1-38-9) drotreated light (CAS 6474			
US. Massachusetts RTK - Substance List				
n-hexane (CAS 110-54-3	drotreated light (CAS 647، 3)	,		
US. Pennsylvania Worker a	nd Community Right-to	-Know Law		
acetone (CAS 67-64-1) carbon dioxide (CAS 124 naphtha (petroleum), hyo n-hexane (CAS 110-54-3 US. Rhode Island RTK	drotreated light (CAS 647	42-49-0)		
acetone (CAS 67-64-1) carbon dioxide (CAS 124 naphtha (petroleum), hyo	drotreated light (CAS 647	42-49-0)		
n-hexane (CAS 110-54-3	3)			

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 6	5 - CRT: Listed date/Carcir	nogenic substance	
acetaldehyde (CAS 75-07-0) benzene (CAS 71-43-2) cumene (CAS 98-82-8) ethylbenzene (CAS 100-41-4)		Listed: April 1, 1988 Listed: February 27, 1987 Listed: April 6, 2010 Listed: June 11, 2004	
, , , , , , , , , , , , , , , , , , ,	5 - CRT: Listed date/Devel		
benzene (CAS 71-43 methanol (CAS 67-5 toluene (CAS 108-88	3-2) 6-1)	Listed: December 26, 1997 Listed: March 16, 2012 Listed: January 1, 1991	
California Proposition 6	55 - CRT: Listed date/Male r	reproductive toxin	
benzene (CAS 71-43 n-hexane (CAS 110-		Listed: December 26, 1997 Listed: December 15, 2017	
Volatile organic compounds (VC	DC) regulations		
EPA			
VOC content (40 CFR 51.100(s))	46.3 %		
Consumer products (40 CFR 59, Subpt. C)	Not regulated		
State			
Consumer products	This product is regulated as a General Purpose Degreaser (aerosol). This product is not compliant to be sold for use in California, Colorado, Connecticut, Delaware, Maryland, Michigan, New Hampshire, New York, Rhode Island, and the following counties in Utah: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber. This product is compliant in all other states.		
VOC content (CA)	46.3 %		
VOC content (OTC)	46.3 %		
International Inventories			
Country(s) or region	Inventory name		On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS) Yes		
Canada			Yes
Canada	Non-Domestic Substances List (NDSL) N		
China	Inventory of Existing Chemical Substances in China (IECSC) Ye		
Europe	European Inventory of Exis Substances (EINECS)	sting Commercial Chemical	Yes
Europe	European List of Notified C	Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and N	lew Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL) Y		Yes
New Zealand	New Zealand Inventory		Yes
Philippines	Philippine Inventory of Che (PICCS)	emicals and Chemical Substances	Yes
Taiwan	Taiwan Chemical Substan	ce Inventory (TCSI)	Yes
United States & Puerto Rico			Yes
*A "Vaa" indicates that all some	aanta of this product comply with	the inventory requirements administered by th	a coverning country(a)

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	12-31-2019
Revision date	04-04-2023
Prepared by	Allison Yoon
Version #	04
Further information	CRC # 463D-E/1002463-1008113

Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	Product and Company Identification: Product and Company Identification Composition / Information on Ingredients: Disclosure Overrides Physical & Chemical Properties: Multiple Properties Stability and reactivity: Incompatible materials Disposal considerations: Disposal instructions Disposal considerations: Hazardous waste code Regulatory information: Consumer products