

SAFETY DATA SHEET

1. Identification

Product identifier	Jump Start® Starting Fluid - 11 oz	
Other means of identification		
Product Code	No. 05671 (Item# 1003843)	
Recommended use	Starting fluid	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/	Distributor information	
Manufactured or sold by:		
Company name	CRC Industries, Inc.	
Address	885 Louis Dr.	
	Warminster, PA 18974 US	
Telephone		
General Information	215-674-4300	
Technical Assistance	800-521-3168	
Customer Service	800-272-4620	
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)	
Website	www.crcindustries.com	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Carcinogenicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 3
	Not classified.	
OSHA defined hazards		

Signal word Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Danger

Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
heptane, branched, cyclic and linear		426260-76-6	70 - 80
diethyl ether		60-29-7	10 - 20
carbon dioxide		124-38-9	5 - 10
ethanol		64-17-5	< 1.5
chloroethane		75-00-3	≤ 1
distillates (petroleum), hydrotreated light		64742-47-8	≤ 1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

 emergency procedures confined areas (sewers, basements, tanks) during clean-up. Avoid breathing mist or val breathing equipment. Do not touch damage appropriate protective clothing. Ventilate cle should be advised if significant spillages ca Eliminate all ignition sources (no smoking, f combustibles (wood, paper, oil, etc.) away f Prevent product from entering drains. Stop absorbent material (e.g. cloth, fleece). Clea Put material in suitable, covered, labeled cor Environmental precautions 	kage or spillage if safe to do so. Avoid discharge into
 emergency procedures confined areas (sewers, basements, tanks) during clean-up. Avoid breathing mist or val breathing equipment. Do not touch damage appropriate protective clothing. Ventilate cle should be advised if significant spillages ca Eliminate all ignition sources (no smoking, from containment and cleaning up) Prevent product from entering drains. Stop absorbent material (e.g. cloth, fleece). Clean 	propriate managerial or supervisory personnel of all
emergency procedures during clean-up. Avoid breathing mist or val breathing equipment. Do not touch damage appropriate protective clothing. Ventilate clo	lares, sparks, or flames in immediate area). Keep rom spilled material. This product is miscible in water. the flow of material, if this is without risk. Wipe up with n surface thoroughly to remove residual contamination. ntainers.
	eople away from and upwind of spill/leak. Keep out of and will spread along ground and collect in low or Wear appropriate protective equipment and clothing bor. Emergency personnel need self-contained d containers or spilled material unless wearing used spaces before entering them. Local authorities anot be contained.

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
chloroethane (CAS 75-00-3)	PEL	2600 mg/m3	
		1000 ppm	
diethyl ether (CAS 60-29-7)	PEL	1200 mg/m3	
		400 ppm	
ethanol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	

US. ACGIH Threshold Limi Components	Туре	Value
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
chloroethane (CAS 75-00-3)	TWA	100 ppm
diethyl ether (CAS 60-29-7)	STEL	500 ppm
	TWA	400 ppm
ethanol (CAS 64-17-5)	STEL	1000 ppm
US. NIOSH: Pocket Guide t	o Chemical Hazards	
Components	Туре	Value
carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3
,		30000 ppm
	TWA	9000 mg/m3
		5000 ppm
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3
ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
logical limit values	No biological exposure limits note	d for the ingredient(s).
oosure guidelines		
US - California OELs: Skin	-	
chloroethane (CAS 75-0 US ACGIH Threshold Limit		an be absorbed through the skin.
chloroethane (CAS 75-0	0-3) Da	anger of cutaneous absorption
propriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.	
ividual protection measures	, such as personal protective equi	pment
Eye/face protection	Wear safety glasses with side shie	elds (or goggles).
Skin protection		
Hand protection	Wear protective gloves such as: N	litrile. Butyl rubber.
Other	Wear appropriate chemical resista	int clothing.
Respiratory protection	NIOSH-approved cartridge respira	sible or if exposure exceeds the applicable exposure limits, use tor with an organic vapor cartridge. Use a self-contained baces and for emergencies. Air monitoring is needed to ure levels.
Thermal hazards	Wear appropriate thermal protecti	ve clothing, when necessary.
neral hygiene nsiderations	personal hygiene measures, such	requirements. When using do not smoke. Always observe good as washing after handling the material and before eating, ely wash work clothing and protective equipment to remove

. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Colorless.
Odor	Hydrocarbon-like.
Odor threshold	Not available.

рН	Not available.
Melting point/freezing point	-189.9 °F (-123.3 °C) estimated
Initial boiling point and boiling range	94.3 °F (34.6 °C) estimated
Flash point	-58.0 °F (-50.0 °C) estimated
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	osive limits
Explosive limit - lower (%)	0.5 % estimated
Explosive limit - upper (%)	36.5 % estimated
Vapor pressure	5901.2 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.7
Solubility(ies)	
Solubility (water)	Slightly soluble.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	356 °F (180 °C) estimated
Decomposition temperature	Not available.
Viscosity	< 20 cSt (104 °F (40 °C))
Percent volatile	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Aluminum.
Hazardous decomposition products	Carbon oxides. Acrid smoke.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.	
Skin contact	Causes skin irritation.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.	
Information on toxicological effects		

Acute toxicity	May be fatal if swallowed and enters airways.		
Components	Species	Test Results	
diethyl ether (CAS 60-29-7)			
Acute			
Oral			
LD50	Rat	3230 - 3920 mg/kg	
LD50	Rat	3230 - 3920 mg/kg	

Components	Species	Test Results		
ethanol (CAS 64-17-5)				
Acute				
Dermal				
LD50	Rabbit	20 g/kg		
Inhalation LC50	Rat	8000 mg/l, 4 hours		
EC30	Nat	8000 mg/i, 4 nouis		
* Estimates for product may b	be based on additional compone	ent data not shown.		
Skin corrosion/irritation	Causes skin irritation.			
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.			
Respiratory or skin sensitizatio	n			
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	This product is not expected	to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate mutagenic or genotoxic.	product or any components present at greater than 0.1% are		
Carcinogenicity	Suspected of causing cance			
IARC Monographs, Overall	Evaluation of Carcinogenicity	I		
chloroethane (CAS 75-0 diethyl ether (CAS 60-29	0-3)	3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans.		
	ed Substances (29 CFR 1910.	U I		
	ogram (NTP) Report on Carci	nogens		
Reproductive toxicity	This product is not expected	to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.			
Specific target organ toxicity -	Not classified.	Not classified.		
repeated exposure				
Aspiration hazard		d enters airways. If aspirated into lungs during swallowing or vomiting, onia, pulmonary injury or death.		
Chronic effects	Prolonged inhalation may be	harmful.		
12. Ecological informatio	n			
Ecotoxicity	Toxic to aquatic life. Harmful	to aquatic life with long lasting effects.		
Persistence and degradability	·			
Bioaccumulative potential				
Partition coefficient n-octa	nol / water (log Kow)			
chloroethane		1.43		
diethyl ether	0.89			
ethanol		-0.31		
Mobility in soil	No data available.			
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
13. Disposal consideration	ons			
Disposal instructions	waste code of D001 (See 40 partially-full aerosol cans can the material under controlled containers. Do not allow this	is a RCRA hazardous waste for the characteristic of ignitability with a CFR Part 261.20 – 261.33). Empty container can be recycled. Full or be treated as universal waste. Contents under pressure. Incinerate conditions in an approved incinerator. Do not incinerate sealed material to drain into sewers/water supplies. Do not contaminate with chemical or used container. Dispose in accordance with all		

ponds, waterways or ditches with chemical or used container. Dispose in accordance with all

applicable regulations.


Hazardous waste code	Possible RCRA waste code includes: D001: Waste Flammable material with a flash point <140 F
	However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN1950 UN proper shipping name Aerosols, flammable, Limited Quantity Transport hazard class(es) 2.1 Class Subsidiary risk _ Label(s) 2.1 Packing group Not assigned. **Environmental hazards** Marine pollutant No. Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Special provisions N82 **Packaging exceptions** 306 None Packaging non bulk Packaging bulk None ΙΑΤΑ **UN number** UN1950 UN proper shipping name Aerosols, flammable, Limited Quantity Transport hazard class(es) Class 2.1 Subsidiary risk Not assigned. Packing group **ERG Code** 10L Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Other information Passenger and cargo Allowed with restrictions. aircraft Allowed with restrictions. Cargo aircraft only IMDG **UN number** UN1950 UN proper shipping name AEROSOLS, Limited Quantity Transport hazard class(es) Class 2.1 Subsidiary risk Packing group Not assigned. **Environmental hazards** Marine pollutant No. F-D, S-U EmS Special precautions for user Read safety instructions, SDS and emergency procedures before handling.







15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

chloroethane (CAS 75-00-3) diethyl ether (CAS 60-29-7)

CERCLA Hazardous Substances: Reportable quantity

chloroethane (CAS 75-00-3)	100 LBS
diethyl ether (CAS 60-29-7)	100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Other rederal regulations		
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutar	nts (HAPs) List
chloroethane (CAS 75-00)-3)	
Clean Air Act (CAA) Section	n 112(r) Accidental Release I	Prevention (40 CFR 68.130)
chloroethane (CAS 75-00 diethyl ether (CAS 60-29-	,	
Safe Drinking Water Act (SDWA)	Not regulated.	
Drug Enforcement Adm Chemical Code Number		sential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and
diethyl ether (CAS 6	0-29-7)	6584
•		Exempt Chemical Mixtures (21 CFR 1310.12(c))
diethyl ether (CAS 6	0-29-7)	35 %WV
DEA Exempt Chemical	Mixtures Code Number	
diethyl ether (CAS 6	0-29-7)	6584
FEMA Priority Substand	ces Respiratory Health and S	Safety in the Flavor Manufacturing Workplace
ethanol (CAS 64-17-	5)	Low priority
Food and Drug Administration (FDA)	Not regulated.	
Superfund Amendments and Re	authorization Act of 1986 (S	ARA)
Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Gas under pressure Skin corrosion or irritation Carcinogenicity Specific target organ toxicity (single or repeated exposure) Aspiration hazard	
SARA 302 Extremely hazard Not listed.	dous substance	
SARA 311/312 Hazardous chemical	Yes	

SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
chloroethane		75-00-3	≤ 1	
S state regulations				
US. California. Candidate Cl	hemicals List. Safe	er Consumer Products Re	gulations (Cal. Code F	Regs, tit. 22, 69502.3, subd.
(a)) chloroethane (CAS 75-00	13)			
diethyl ether (CAS 60-29-				
distillates (petroleum), hy	drotreated light (CA			
US. New Jersey Worker and		t-to-Know Act		
carbon dioxide (CAS 124 chloroethane (CAS 75-00				
diethyl ether (CAS 60-29-				
ethanol (CAS 64-17-5)				
US. Massachusetts RTK - Su				
carbon dioxide (CAS 124 chloroethane (CAS 75-00				
diethyl ether (CAS 60-29-				
ethanol (CAS 64-17-5)	ad Community Dia	ht to Know Low		
US. Pennsylvania Worker ar carbon dioxide (CAS 124-				
chloroethane (CAS 75-00				
diethyl ether (CAS 60-29-				
distillates (petroleum), hy ethanol (CAS 64-17-5)	drotreated light (CA	S 64742-47-8)		
US. Rhode Island RTK				
carbon dioxide (CAS 124	-38-9)			
chloroethane (CAS 75-00				
diethyl ether (CAS 60-29- distillates (petroleum), hy		S 64742-47-8)		
ethanol (CAS 64-17-5)		0 0 1 1 2 1 1 0)		
California Proposition 65				
WARNING: Ca	ancer and Reproduc	ctive Harm - www.P65Warn	ings.ca.gov	
California Proposition 6	5 - CRT: Listed da	te/Carcinogenic substanc	ce	
chloroethane (CAS 7	(5-00-3)	Listed: July 1	, 1990	
California Proposition 6		•		
toluene (CAS 108-88	,	Listed: Janua	ary 1, 1991	
blatile organic compounds (VC EPA)C) regulations			
VOC content (40 CFR 51.100(s))	94.5 %			
Consumer products	Not regulated			
(40 CFR 59, Subpt. C)	Not regulated			
State				
Consumer products	Not regulated			
VOC content (CA)	94.5 %			
VOC content (OTC)	94.5 %			
ternational Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Invento	ory of Industrial Chemicals ((AICIS)	No
Canada	Domestic Substar	nces List (DSL)		Yes
Canada		ıbstances List (NDSL)		No
China	•	ing Chemical Substances ir	· · · ·	No
Europe	European Invento Substances (EIN	ory of Existing Commercial (Chemical	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	11-18-2022
Prepared by	Allison Yoon
Version #	01
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	This document has undergone significant changes and should be reviewed in its entirety.