

SAFETY DATA SHEET

1. Identification

Product identifier Lectra Clean® 3000 Energized Electrical Equipment Cleaner - 1 lb 3 oz

Other means of identification

Item# 1750521 **Product Code**

Recommended use Energized electrical cleaner

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical Assistance** 800-521-3168 800-272-4620 **Customer Service** 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Compressed gas Gases under pressure **Health hazards** Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 2B Sensitization, skin Category 1B Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Category 2

Category 2

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word

Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic **Hazard statement**

skin reaction. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Material name: Lectra Clean® 3000 Energized Electrical Equipment Cleaner - 1 lb 3 oz Item# 1750521 Version #: 01 Issue date: 07-01-2021

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned:

Get medical advice/attention.

Storage Protect from sunlight. Store in a well-ventilated place. Keep container tightly closed. Store locked

up. Exposure to high temperature may cause can to burst.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal

corrosive gases such as hydrogen chloride and possibly phosgene.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
tetrachloroethylene	perchloroethylene	127-18-4	90 - 100
carbon dioxide		124-38-9	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Cymptoms may be aciayed.

General informationIF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated

clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Dry chemical, CO2, or water spray.

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

Unsuitable extinguishing media

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

General fire hazards

Firefighters must use standard protective equipment including flame retardant coat, helmet with

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without

Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

risk. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Collect spillage. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Store in tightly closed container. Store in a well-ventilated place. Exposure to high temperature may cause can to burst. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
US. OSHA Table Z-2 (29 CFR 1910	0.1000)	
Components	Туре	Value
tetrachloroethylene (CAS 127-18-4)	Ceiling	200 ppm
	TWA	100 ppm
US. ACGIH Threshold Limit Value	es	
Components	Туре	Value
carbon dioxide (CAS 124-38-9)	STEL	30000 ppm

Components	Тур	ре	V	alue	
	TW	/A	50	000 ppm	
tetrachloroethylene (CAS 127-18-4)	STI	EL	10	00 ppm	
	TW	/A	2	5 ppm	
US. NIOSH: Pocket Guide	to Chemical Hazard	s			
Components	Туј	oe	V	alue	
carbon dioxide (CAS 124-38-9)	ST	EL	54	4000 mg/m3	
			30	0000 ppm	
	TW	/A	9	000 mg/m3	
			50	000 ppm	
US. California Code of Re	egulations, Title 8, Se	ction 5155. Airborne	Contaminant	S	
Components	Тур	oe	V	alue	
carbon dioxide (CAS 124-38-9)	PE	L	9	000 mg/m3	
			50	000 ppm	
	ST	EL	5-	4000 mg/m3	
			30	0000 ppm	
tetrachloroethylene (CAS 127-18-4)	Cei	iling	30	00 ppm	
	PE	L	1	70 mg/m3	
			2	5 ppm	
	ST	EL	6	35 mg/m3	
			10	00 ppm	
logical limit values					
ACGIH Biological Exposi	ure Indices				
Components	Value	Determinant	Specimen	Sampling Time	
tetrachloroethylene (CAS	0.5 mg/l	Tetrachloroethy	Blood	*	_

Biol

Components	Value	Determinant	Specimen	Sampling Time
tetrachloroethylene (CAS 127-18-4)	0.5 mg/l	Tetrachloroethy lene	Blood	*
	3 ppm	Tetrachloroethy lene	End-exhaled air	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - Minnesota Haz Subs: Skin designation applies

tetrachloroethylene (CAS 127-18-4)

Skin designation applies.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Nitrile. Polyvinyl alcohol (PVA). Viton/butyl. Silver Shield®. **Hand protection**

Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary. General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Aerosol. Color Colorless. Irritating. Odor **Odor threshold** 50 ppm Not available. pН

Melting point/freezing point -8.1 °F (-22.3 °C) estimated Initial boiling point and boiling 248 °F (120 °C) estimated

range

None (Tag Closed Cup) Flash point

Evaporation rate Very fast. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

1232.1 hPa estimated Vapor pressure

5.76 (air = 1) Vapor density

Relative density 1.62

Solubility(ies)

0.02 % (77 °F (25 °C)) Solubility (water)

Partition coefficient

Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity** Percent volatile 97.9 % estimated

Other information

3.4 Partition coefficient

(oil/water)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Heat, flames and sparks. Contact with incompatible materials. When exposed to extreme heat or Conditions to avoid

hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen

chloride and possibly phosgene.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases.

Hazardous decomposition Hydrogen chloride. Trace amounts of chlorine and phosgene. Carbon oxides. Halogenated

materials. Carbonyl halides. products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes eye irritation.

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea,

and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness or dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Exposed individuals may experience eye tearing, redness, and discomfort. Irritation of nose and throat. Skin irritation. May cause redness and pain. May cause an allergic skin

reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity None known.

Skin corrosion/irritation Causes skin irritation.
Serious eye damage/eye Causes eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

tetrachloroethylene (CAS 127-18-4)

2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

tetrachloroethylene (CAS 127-18-4)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityToxic to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

tetrachloroethylene 3.4

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This material and its container must be disposed of as hazardous waste. Consult authorities before

disposal. Contents under pressure. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in

accordance with all applicable regulations.

Hazardous waste code D039: Waste Tetrachloroethylene

F001: Waste Halogenated Solvent - Spent Halogenated Solvent Used in Degreasing

F002: Waste Halogenated Solvent - Spent Halogenated Solvent

US RCRA Hazardous Waste U List: Reference

tetrachloroethylene (CAS 127-18-4) U210

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN1950 **UN** number

Aerosols, poison, Limited Quantity **UN** proper shipping name

Transport hazard class(es)

Class 2.2 Subsidiary risk 6.1 Label(s) 2.2, 6.1

Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Forbidden from

transportation by air.

Packaging exceptions 306 Packaging non bulk None None Packaging bulk

IATA

UN number UN1950

Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III **UN proper shipping name**

Transport hazard class(es)

Class 2.2 Subsidiary risk 6.1 Packing group 2P **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1950 **UN** proper shipping name **AEROSOLS**

Transport hazard class(es)


Class 2.2 Subsidiary risk 6.1 **Packing group**


Environmental hazards

No. Marine pollutant F-D. S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT





15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

tetrachloroethylene (CAS 127-18-4)

CERCLA Hazardous Substances: Reportable quantity

tetrachloroethylene (CAS 127-18-4) 100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

tetrachloroethylene (CAS 127-18-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Gas under pressure

categories Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
tetrachloroethylene	127-18-4	90 - 100	

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

carbon dioxide (CAS 124-38-9)

tetrachloroethylene (CAS 127-18-4) **US. Massachusetts RTK - Substance List**

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9)

tetrachloroethylene (CAS 127-18-4)

US. Rhode Island RTK

carbon dioxide (CAS 124-38-9) tetrachloroethylene (CAS 127-18-4)

California Proposition 65



WARNING: Cancer - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

tetrachloroethylene (CAS 127-18-4) Listed: April 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

tetrachloroethylene (CAS 127-18-4)

Volatile organic compounds (VOC) regulations

VOC content (40 CFR

0 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C) Not regulated

Inventory name

State

Consumer products

This product is regulated as an Energized Electrical Cleaner for the following states: Connecticut, Delaware, District of Columbia, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and Virginia. It is for energized equipment use only. It is not to be used for motorized vehicle maintenance or their parts. This product is compliant for use in all 50 states.

0 % VOC content (CA) **VOC content (OTC)** 0 %

International Inventories

Country(s) or region

Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes New Zealand **New Zealand Inventory** No **Philippines** Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

07-01-2021 Issue date Danica Fulmer Prepared by

Version # 01

Further information CRC # 491G/1002481 On inventory (yes/no)*

Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information

This document has undergone significant changes and should be reviewed in its entirety.