

SAFETY DATA SHEET

1. Identification

Product identifier	Brakleen® Brake Parts Cleaner - 1 lb 3 oz	
Other means of identification		
Product Code	No. 05084PS (Item# 1008010)	
Recommended use	Brake parts cleaner	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier	/Distributor information	
Manufactured or sold by:		
Company name	CRC Industries, Inc.	
Address	885 Louis Dr.	
	Warminster, PA 18974 US	
Telephone		
General Information	215-674-4300	
Technical Assistance	800-521-3168	
Customer Service	800-272-4620	
24-Hour Emergency	800-424-9300 (US)	
(CHEMTREC) Website	crcindustries.com	
2. Hazard(s) identification	1	
Physical hazards	Flammable aerosols	Category 1
-	Gases under pressure	Compressed gas
lealth hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement		nder pressure; may explode if heated. May be fatal i itation. Causes serious eye irritation. May cause
Precautionary statement		
Prevention	flame or other ignition source. Pressurized cor not apply while equipment is energized. Exting accumulate readily and may ignite. Use only o	gone. Open doors and windows or use other means hile product is drying. If you experience any tion or leave the area. Avoid breathing mist or

vapor. Wash thoroughly after handling. Wear eye protection/face protection. Wear protective

gloves.

Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
acetone		67-64-1	50 - 60
naphtha (petroleum), hydrotreated light		64742-49-0	20 - 30
n-heptane		142-82-5	10 - 20
carbon dioxide		124-38-9	5 - 10
heptane, branched, cyclic and linear		426260-76-6	5 - 10
solvent naphtha (petroleum), light aliph.		64742-89-8	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.		
Skin contact Remove contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Ge advice/attention. Wash contaminated clothing before reuse.			
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.		
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.		
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.		
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Alcohol resistant foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide,		

Suitable extinguishing media	sand or earth may be used for small fires only.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Minimize fire risks from flammable and combustible materials (including combustible dust and

Precautions for sale handling	static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
carbon dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3	
		100 ppm	
n-heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	

US. OSHA Table Z-1 Limit Components	ts for Air Contaminan Typ			lue	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	PEL	-	40	0 mg/m3	
(0/10/01/12/00/0)			10	0 ppm	
US. ACGIH Threshold Lin	nit Values				
Components	Тур	e	Va	lue	
acetone (CAS 67-64-1)	STE	EL	50	0 ppm	
	TW	A	25	0 ppm	
carbon dioxide (CAS 124-38-9)	STE	EL	30	000 ppm	
	TW			00 ppm	
n-heptane (CAS 142-82-5)	STE			0 ppm	
	TW	A	40	0 ppm	
US. NIOSH: Pocket Guide Components	e to Chemical Hazards Typ		Va	lue	
acetone (CAS 67-64-1)	TW	A	59	0 mg/m3	
			25	0 ppm	
carbon dioxide (CAS	STE	EL	54	000 mg/m3	
124-38-9)			30	000 ppm	
	TW	A	90	00 mg/m3	
			50	00 ppm	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TW	A	40	0 mg/m3	
			10	0 ppm	
n-heptane (CAS 142-82-5)	Ceil	ling		00 mg/m3	
				0 ppm	
	TW	A		0 mg/m3	
				ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TW	A	40	0 mg/m3	
()			10	0 ppm	
ogical limit values					
ACGIH Biological Exposu	ire Indices				
Components	Value	Determinant	Specimen	Sampling Time	
acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
* - For sampling details, ple					
propriate engineering trols	should be matched or other engineerin	d to conditions. If ap ng controls to mainta	plicable, use pro ain airborne level	nour) should be used. Ventil cess enclosures, local exha s below recommended expo borne levels to an acceptab	ust ventilation, osure limits. If
vidual protection measure	es, such as personal p	protective equipme	ent		
Eye/face protection	Wear safety glass	es with side shields	(or goggles).		
Skin protection					
Hand protection	Wear protective al	oves such as: Nitrile	. Neoprene. Poly	vinyl alcohol (PVA).	

Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

•	• •
Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Colorless.
Odor	Solvent.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	-139.6 °F (-95.4 °C) estimated
Initial boiling point and boiling range	132.8 °F (56 °C) estimated
Flash point	0 °F (-17.8 °C) estimated
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	1 % estimated
Explosive limit - upper (%)	14.3 % estimated
Vapor pressure	4779.1 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.81 estimated
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	433 °F (222.8 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Percent volatile	100 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.

Eye contact	Causes serious eye irritation.	
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.	
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.	
Information on toxicological eff	ects	
Acute toxicity	May be fatal if swallowed and enters airways.	
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity Not listed. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Not listed.		
US. National Toxicology Pro Not listed.	ogram (NTP) Report on Carcinogens	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information	n	
Ecotoxicity	Very toxic to aquatic life with long lasting effects.	
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Partition coefficient n-octar	iol / water (log Kow)	
acetone	-0.24	
n-heptane	4.66	
Bioconcentration factor (BC naphtha (petroleum), hydrotre		
Mobility in soil	No data available.	
Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.	
13. Disposal consideratio		
•	This material and its container must be disposed of as hazardous waste. Full or partially-full	
Disposal instructions	aerosol cans can be treated as universal waste. Empty container can be recycled. Contents under pressure. Do not incinerate sealed containers. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.	
Hazardous waste code	Possible RCRA waste code includes: D001: Waste Flammable material with a flash point <140 F F003: Waste Non-halogenated Solvent - Spent Non-halogenated Solvent	
	However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.	

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not assigned.
Environmental hazards	5
Marine pollutant	No.
•	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not assigned.
ERG Code	10L
· ·	• Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not assigned.


 Environmental hazards

 Marine pollutant
 Yes, but exempt from the regulations.

 EmS
 F-D, S-U

 Special precautions for user
 Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

acetone (CAS 67-64-1)

CERCLA Hazardous Substances: Reportable quantity

acetone (CAS 67-64-1)

5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

acetone (CAS 67-64-1)

acetone (CAS 67-64-1)

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

35 %WV

DEA Exempt Chemical Mixtures Code Number

acetone (CAS 67-64-1) 6532

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Low priority

acetone (CAS 67-64-1)
Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Gas under pressure Skin corrosion or irritation Serious eye damage or eye irritation Specific target organ toxicity (single or repeated exposure) Aspiration hazard Hazard not otherwise classified (HNOC)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a)) acetone (CAS 67-64-1) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) US. New Jersey Worker and Community Right-to-Know Act acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) **US. Massachusetts RTK - Substance List** acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) US. Pennsylvania Worker and Community Right-to-Know Law acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) **US. Rhode Island RTK** acetone (CAS 67-64-1) carbon dioxide (CAS 124-38-9) naphtha (petroleum), hydrotreated light (CAS 64742-49-0) n-heptane (CAS 142-82-5) solvent naphtha (petroleum), light aliph. (CAS 64742-89-8) **California Proposition 65** WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov California Proposition 65 - CRT: Listed date/Carcinogenic substance acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 benzene (CAS 71-43-2) Listed: February 27, 1987 cumene (CAS 98-82-8) Listed: April 6, 2010 ethylbenzene (CAS 100-41-4) Listed: June 11, 2004 Listed: April 19, 2002 naphthalene (CAS 91-20-3) California Proposition 65 - CRT: Listed date/Developmental toxin Listed: December 26, 1997 benzene (CAS 71-43-2) methanol (CAS 67-56-1) Listed: March 16, 2012 toluene (CAS 108-88-3) Listed: January 1, 1991 California Proposition 65 - CRT: Listed date/Male reproductive toxin benzene (CAS 71-43-2) Listed: December 26, 1997 n-hexane (CAS 110-54-3) Listed: December 15, 2017 Volatile organic compounds (VOC) regulations **EPA** VOC content (40 CFR 40.5 % 51.100(s))

Consumer products Not regulated (40 CFR 59, Subpt. C)

This product is regulated as a Brake Cleaner. This product is not compliant to be sold for use in **Consumer products** California, Colorado, Connecticut, Delaware, Maryland, Michigan, New Hampshire, New York, Rhode Island, and the following counties in Utah: Box Elder, Cache, Davis, Salt Lake, Tooele, Utah, and Weber. This product is compliant in all other states. VOC content (CA) 40.5 % 40.5 % VOC content (OTC) International Inventories Country(s) or region On inventory (yes/no)* Inventory name Australia Australian Inventory of Industrial Chemicals (AICIS) No Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) No European Inventory of Existing Commercial Chemical Europe No Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory No Philippines Philippine Inventory of Chemicals and Chemical Substances Yes (PICCS) Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

State

-
12-31-2019
04-04-2023
Allison Yoon
04
CRC # 942A/1002959
The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Product and Company Identification: Product and Company Identification Hazard(s) identification: Hazard statement Composition / Information on Ingredients: Disclosure Overrides Physical & Chemical Properties: Multiple Properties Disposal considerations: Disposal instructions Disposal considerations: Hazardous waste code Regulatory information: Consumer products