



1. Identification

Product identifier	QD® Electronic Cleaner - 11 oz	
Other means of identification		
Product Code	No. 05103 (Item# 1003719)	
Recommended use	Electronic cleaner	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Manufactured or sold by:		
Company name	CRC Industries, Inc.	
Address	885 Louis Dr.	
	Warminster, PA 18974 US	
Telephone	800-556-5074	
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)	
Website	crcindustries.com	

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility or the unborn child.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only outdoors or in a well-ventilated area. Maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist/vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
naphtha (petroleum), hydrotreated light		64742-49-0	70 - 80
1,1-difluoroethane	HFC-152a	75-37-6	20 - 30

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Suitable extinguishing media Unsuitable extinguishing media	
Unsuitable extinguishing	be used for small fires only.
Unsuitable extinguishing media Specific hazards arising from	 be used for small fires only. Do not use water jet as an extinguisher, as this will spread the fire. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may
Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment	 be used for small fires only. Do not use water jet as an extinguisher, as this will spread the fire. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. Firefighters must use standard protective equipment including flame retardant coat, helmet with
Unsuitable extinguishing media Specific hazards arising from the chemical Special protective equipment and precautions for firefighters Fire-fighting	 be used for small fires only. Do not use water jet as an extinguisher, as this will spread the fire. Contents under pressure. Pressurized container may rupture when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Remove all possible sources of ignition in the surrounding area. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Prevent product from entering drains. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage,	Level 3 Aerosol.
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for A Components	Туре	Value	
naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m3	
		100 ppm	
		1 1	
US. NIOSH: Pocket Guide to Che	emical Hazards		
US. NIOSH: Pocket Guide to Che Components	emical Hazards Type	Value	

Components	ental Exposure Level (WEEL) Guides Type	Value	
1,1-difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3	
		1000 ppm	
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower should be available when handling this product.		
Individual protection measure	s, such as personal protective equipn	nent	
Eye/face protection	Wear safety glasses with side shield	s (or goggles).	
Skin protection Hand protection	Wear protective gloves such as: Nitr	ile. Polyvinyl chloride (PVC). Viton/butyl.	
Other	Wear appropriate chemical resistant		
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.		
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
General hygiene considerations		bserve good personal hygiene measures, such as washing e eating, drinking, and/or smoking. Routinely wash work remove contaminants.	

9. Physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Aerosol.
Color	Colorless.
Odor	Alcoholic.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	137 °F (58.3 °C) estimated
Flash point	-0.4 °F (-18.0 °C) estimated
Evaporation rate	Very fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	1 % estimated
Explosive limit - upper (%)	7.8 % estimated
Vapor pressure	Not available.
Vapor pressure temp.	68 °F (20 °C)
Vapor density	>1 (air = 1)
Relative density	0.72 estimated
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	550.4 °F (288 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Aluminum.
Hazardous decomposition products	Aldehydes. Carbon oxides. Carbonyl fluoride. Fluorocarbons. Formaldehyde. Hydrocarbon fumes and smoke. Hydrogen fluoride.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms related to the physical, chemical and toxicological characteristics	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	May be fatal if swallowed and enters airways.
----------------	---

·····,	5	,
Components	Species	Test Results
1,1-difluoroethane (CAS 75-37-6)		
Acute		
Inhalation		
LC50	Mouse	369000 ppm, 2 Hours
naphtha (petroleum), hydrotreated	d light (CAS 64742-49-0)	
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Inhalation		
Vapor		
LC50	Rat	> 5.200000000000002 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause	e skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity	to humans.
IARC Monographs. Overall	Evaluation of Carcinogenicity	
Not listed.		
OSHA Specifically Regulate	ed Substances (29 CFR 1910.1001-10	53)
Not listed.		
••	ogram (NTP) Report on Carcinogens	
Not listed.		

Reproductive toxicity	Suspected of damaging fertility or the unborn child.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information	I	
Ecotoxicity	Toxic to aquatic life with long lasting effects.	
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Partition coefficient n-octan	ol / water (log Kow) 0.75	
Bioconcentration factor (BC naphtha (petroleum), hydrotre	F)	
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	
13. Disposal consideration	ns	
Disposal instructions	The dispensed liquid product is a RCRA hazardous waste for the characteristic of ignitability with a waste code of D001 (See 40 CFR Part 261.20 – 261.33). Full or partially-full aerosol cans can be treated as universal waste. Empty container can be recycled. Contents under pressure. Do not incinerate sealed containers. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.	
Hazardous waste code	waste codePossible RCRA waste code includes: D001: Waste Flammable material with a flash point <140 F	
	However, it is the generator's responsibility to determine the proper classification and disposal method at the time of disposal.	
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.	


14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not assigned.
Environmental hazards	
Marine pollutant	Yes, but exempt from regulations.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not assigned.

	ERG Code	10L
	Special precautions for user Other information	Read safety instructions, SDS and emergency procedures before handling.
	Passenger and cargo aircraft	Allowed with restrictions.
	Cargo aircraft only	Allowed with restrictions.
IME)G	
	UN number	UN1950
	UN proper shipping name	AEROSOLS, Limited Quantity
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Packing group	Not assigned.
	Environmental hazards	
	Marine pollutant	Yes, but exempt from regulations.
	EmS	F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-difluoroethane (CAS 75-37-6)

Safe Drinking Water Act	Not regulated.
(SDWA)	
Food and Drug	Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard	Flammable (gases, aerosols, liquids, or solids)	
categories	Gas under pressure	
-	Skin corrosion or irritation	
	Serious eye damage or eye irritation	
	Reproductive toxicity	
	Specific target organ toxicity (single or repeated exposure)	
	Aspiration hazard	
	Hazard not otherwise classified (HNOC)	
	Hazard not otherwise classified (HNOC)	

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (CAS 64742-49-0)

US. New Jersey Worker and Community Right-to-Know Act

1,1-DIFLUOROETHANE (CAS 75-37-6) NAPHTHA (CAS 64742-49-0)

- US. Massachusetts RTK Substance List Difluoroethane (CAS 75-37-6) Naphtha (CAS 64742-49-0)
- US. Pennsylvania Worker and Community Right-to-Know Law Naphtha (CAS 64742-49-0)
- US. Rhode Island RTK

VM & P NAPTHA (CAS 64742-49-0)

California Proposition 65

(40 CFR 59, Subpt. C)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 6	5 - CRT: Listed date/Carcino	ogenic substance
acetaldehyde (CAS 75-07-0)		Listed: April 1, 1988
ethylbenzene (CAS 100-41-4)		Listed: June 11, 2004
methyl isobutyl ketone (CAS 108-10-1)		Listed: November 4, 2011
California Proposition 6	5 - CRT: Listed date/Develo	pmental toxin
methanol (CAS 67-56-1)		Listed: March 16, 2012
methyl isobutyl ketone (CAS 108-10-1)		Listed: March 28, 2014
toluene (CAS 108-88-3)		Listed: January 1, 1991
California Proposition 6	5 - CRT: Listed date/Male re	productive toxin
n-hexane (CAS 110-54-3)		Listed: December 15, 2017
Volatile organic compounds (VC	OC) regulations	
EPA		
VOC content (40 CFR 51.100(s))	75 %	
Consumer products	Not regulated	

Material name: QD® Electronic Cleaner - 11 oz No. 05103 (Item# 1003719) Version #: 03 Revision date: 08-18-2023 Issue date: 03-22-2019 State

State		
Consumer products	This product is regulated as an Electronic Cleaner. This product is compliant for use in all 50 states.	
VOC content (CA)	75 %	
VOC content (OTC)	75 %	
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	03-22-2019
Revision date	08-18-2023
Prepared by	Joshua Weir
Version #	03
Further information	CRC # 985/1002984
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision information	Product and Company Identification: Product and Company Identification Hazard(s) identification: Hazard statement Hazard(s) identification: Prevention Composition / Information on Ingredients: Disclosure Overrides Physical & Chemical Properties: Multiple Properties Stability and reactivity: Hazardous decomposition products Disposal considerations: Disposal instructions Disposal considerations: Hazardous waste code Transport Information: Proper Shipping Name/Packing Group GHS: Acute Toxicity Estimate