

SAFETY DATA SHEET

1. Identification

not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri	Product identifier	Duster™	
Recommended use Pressurized gas duster Recommended restrictions None known. Manufacturer/Importer/Supplier/Suplier/Supplier/S	Other means of identification		
Recommended restrictions None known. Manufacturer/Importer/Supplier/Distributor information Manufactured or sold by: Company name CRC Industries, Inc. Address 885 Louis Dr. Address 885 Louis Dr. Warminster, PA 18974 US Telephone 600-521-3168 Customer Service 800-521-3168 Customer Service 800-424-9300 (US) (CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com 2. Hazard(s) identification Gases under pressure Liquefied gas Liquefied gas Health hazards Not classified. OSHA defined hazards Not classified. Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precutionary statement Rece away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flames or other ignition source. Pressure de containers. On ont pierce or bun, even after use. Do not apply while equipuent is energized. Extremely dammasi ugnite. Use only whila dequate ventilation; maintain ventilation duri use and until all vapors are gone. Open doors and windows or use other means to ensure after a supply during use and while produs dring	Product code	No. 05185 (Item# 1003746)	
Manufacturer/Importer/Supplier/Distributor information Manufactured or sold by: Company name CRC Industries, Inc. Address B85 Louis Dr. Warminster, PA 18974 US Telephone General Information 215-674-4300 Technical Assistance 800-272-4620 24-Hour Emergency 800-424-9300 (US) (CHEMTREC) 703-527-3887 (International) Website Www.crcindustries.com Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. Label elements Signal word Hazard statement Prevention Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressure containers, and windows or use other means to ensure a fre use of the ignition source. Or product is drying.	Recommended use	Pressurized gas duster	
Manufactured or sold by: Crompany name CRC Industries, Inc. Address 885 Louis Dr. Warminster, PA 18974 US Telephone 215-674-4300 Sinter State	Recommended restrictions	None known.	
Manufactured or sold by: Crompany name CRC Industries, Inc. Address 885 Louis Dr. Warminster, PA 18974 US Telephone 215-674-4300 Sinter State	Manufacturer/Importer/Supplier	/Distributor information	
Company name CRC Industries, Inc. Address 885 Louis Dr. Warminster, PA 18974 US			
Address 885 Louis Dr. Warminster, PA 18974 US Telephone 215-674-4300 General Information 215-674-4300 Technical Assistance 800-521-3168 Customer Service 800-227-4620 24-Hour Emergency 600-424-9300 (US) (CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. OSHA defined hazards Not classified. OSHA defined hazards Not classified. Signal word Danger Hazard statement Exempt filammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Keep away from heat/sparks/open filames/hot surfaces No smoking. Do not spray on an open filame or other ignition source. Pressure; may explode if heated. Prevention Keep away from heat/sparks/open filames/hot surfaces No smoking. Do not spray on an open filame or other ignition source. Pressure; may explode if heated. Prevention Keep away from heat/sparks/open filames/hot surfaces No smoking. Do not spray on an open filame or other ignition source. Pressure; may explode if heated. weind until all apopos	-	CRC Industries, Inc.	
Telephone 215-674-4300 General Information 215-674-4300 Technical Assistance 800-521-3168 Gustomer Service 800-272-4620 24-Hour Emergency 800-424-9300 (US) (CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. Label elements Danger Signal word Panger Hazard statement Extremely flammable aerosol. Contains gas urder pressure; may explode if heated. Precautionary statement Reep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lifths and heaters. Vapors was accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and while product is dryin.		885 Louis Dr.	
General Information 215-674-4300 Technical Assistance 800-521-3168 Customer Service 800-272-4620 24-Hour Emergency 800-424-9300 (US) (CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Prevention Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors warcumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and while product is drying.		Warminster, PA 18974 US	
Technical Assistance 800-521-3168 Customer Service 800-272-4620 24-Hour Emergency 800-424-9300 (US) (CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com 2. Hazard(s) identification Flarmable aerosols Category 1 Physical hazards Flarmable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. Label elements Danger Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, piol tights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and while product is drying.	Telephone		
Customer Service 800-272-4620 24-Hour Emergency 800-424-9300 (US) (CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com 2. Hazard(s) identification Gases under pressure Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. Label elements Very Correct Correc	General Information	215-674-4300	
24-Hour Emergency (CHEMTREC) 800-424-9300 (US) 703-527-3887 (International) www.crcindustries.com Website www.crcindustries.com 2. Hazard(s) identification Category 1 Gases under pressure Physical hazards Flammable aerosols Gases under pressure Category 1 Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. Vot gas Vot classified. OSHA defined hazards Not classified. Signal word Danger Hazard statement Precautionary statement Prevention Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and unitial alvapors are gone. Open doors and windows or use other means to ensure a fre air supply during use and while product is drying.	Technical Assistance	800-521-3168	
(CHEMTREC) 703-527-3887 (International) Website www.crcindustries.com 2. Hazard(s) identification Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. OSHA defined hazards Not classified. Label elements Vot classified. Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors wa accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and while product is drying.	Customer Service	800-272-4620	
Website www.crcindustries.com 2. Hazard(s) identification Flammable aerosols Category 1 Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. USHA defined hazards Not classified. Label elements Vot classified. Label elements Vot classified. Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Reep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and until all vapors are gone. Open doors and windows or use other means to ensure a fer air supply during use and while product is drying.	24-Hour Emergency	800-424-9300 (US)	
2. Hazard(s) identification Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. Josh defined hazards Not classified. Label elements Vict classified. Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors wa accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.	(CHEMTREC)	703-527-3887 (International)	
Physical hazards Flammable aerosols Category 1 Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. OSHA defined hazards Not classified. Label elements Not classified. Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguisual flames, pilot lights and heaters. Vapors wa accumulate readily and may ignite. Use only with adequate ventilation, maintain ventilation duri use and until all vapors are gone. Open dors and windows or use other means to ensure a fre air supply during use and while product is drying.	Website	www.crcindustries.com	
Gases under pressure Liquefied gas Health hazards Not classified. Environmental hazards Not classified. OSHA defined hazards Not classified. Label elements Vot classified. Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation, maintain ventilation duri use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.	2. Hazard(s) identification	I	
Gases under pressureLiquefied gasHealth hazardsNot classified.Environmental hazardsNot classified.OSHA defined hazardsNot classified.Label elementsImage: Comparing the comparing	Physical hazards	Flammable aerosols	Category 1
Health hazardsNot classified.Environmental hazardsNot classified.OSHA defined hazardsNot classified.Label elementsImage: Comparison of the temperature of t	-	Gases under pressure	Liquefied gas
OSHA defined hazards Not classified. Label elements Image: Comparison of the second of th	Health hazards		
Label elements Image: Comparison of the second of the	Environmental hazards	Not classified.	
Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors wa accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.	OSHA defined hazards	Not classified.	
Signal word Danger Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Precautionary statement Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors wa accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.	Label elements		
Hazard statementExtremely flammable aerosol. Contains gas under pressure; may explode if heated.Precautionary statementKeep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation durin use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.			
Precautionary statementPreventionKeep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation duri use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.	Signal word	Danger	
PreventionKeep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation durin use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.	Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated.	
flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors w accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation durin use and until all vapors are gone. Open doors and windows or use other means to ensure a free air supply during use and while product is drying.	Precautionary statement		
Response Wash hands after handling.	Prevention	flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh	
-	Response	Wash hands after handling.	
Storage Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.	Storage	Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.	
Disposal Dispose of contents/container in accordance with local/regional/national regulations.	Disposal		
Hazard(s) not otherwise classified (HNOC)Deliberately inhaling this product can lead to death from asphyxiation depending on concentrati and duration of exposure.		Deliberately inhaling this product can lead to death from asphyxiation depending on concentration and duration of exposure.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1,1-difluoroethane	HFC-152a	75-37-6	100
4. First-aid measures			
Inhalation	Move to fresh air. Call a physician if symptom	is develop or persist.	
Skin contact	Rinse skin with water/shower. Get medical at	tention if irritation develops and	persists.
Eye contact	Rinse with water. Get medical attention if irrita	ation develops and persists.	
Ingestion	If swallowed, observe for signs of stomach discomfort or nausea. If symptoms persist, seek medical help. Do not induce vomiting. If there is any suspicion of aspiration into lungs, obtain immediate medical attention.		
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporar	y irritation.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and tre	at symptomatically.	
General information	Ensure that medical personnel are aware of the protect themselves.	he material(s) involved, and tak	e precautions to
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carb	on dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as th	is will spread the fire.	
Specific hazards arising from the chemical	Contents under pressure. Pressurized contain During fire, gases hazardous to health may be		to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective eque face shield, gloves, rubber boots, and in enclosed and the state of the sta		nt coat, helmet with

Fire-fighting
equipment/instructionsIn case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without
risk. Containers should be cooled with water to prevent vapor pressure build up.General fire hazardsExtremely flammable aerosol. Contents under pressure. Pressurized container may rupture when
exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many vapors are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke

handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful of fatal. Inhalation abuse can cause death. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
1,1-difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3	
/		1000 ppm	
Biological limit values	No biological exposure limits noted for	r the ingredient(s).	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
Individual protection measures	s, such as personal protective equipm	ent	
Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	Wear protective gloves such as: Insu	ated rubber.	
Other	Wear suitable protective clothing.		
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.		
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.	
General hygiene considerations	after handling the material and before	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Clear.
Odor	Mild petroleum.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	-13 °F (-25 °C)
Flash point	-58 °F (-50 °C) Cleveland Open Cup
Evaporation rate	Fast.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	3.9 %
Flammability limit - upper (%)	16.9 %
Vapor pressure	7841.6 hPa estimated
Vapor density	2.4 (air = 1)
Relative density	0.91 estimated

Material name: Duster™

Solubility (water)	0.28 % @ 70 °F
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	849 °F (453.9 °C)
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	100 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Alkali metals. Alkaline earth metals. Powdered metal.
Hazardous decomposition products	Carbon oxides. Hydrogen fluoride. Carbonyl fluoride. Fluorocarbons.

11. Toxicological information

Information on likely routes of exposure				
Inhalation	Prolonged inhalation may be harmful.			
Skin contact	Prolonged skin contact may cause temporary irritation.			
Eye contact	Direct contact with eyes may cause temporary irritation.			
Ingestion	Health injuries are not known or expected under normal use.			
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.			
Information on toxicological effe	ects			
Acute toxicity	Expected to be a low hazard for usual industrial or commercial handling by trained personnel.			
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.			
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.			
Respiratory sensitization	Not a respiratory sensitizer.			
Skin sensitization	This product is not expected to cause skin sensitization.			
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.			
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.			
Not listed. OSHA Specifically Regulate Not regulated.	Evaluation of Carcinogenicity d Substances (29 CFR 1910.1001-1050) ogram (NTP) Report on Carcinogens			
Not listed.				
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.			
Specific target organ toxicity - single exposure	Not classified.			
Specific target organ toxicity - repeated exposure	Not classified.			
Aspiration hazard	Not expected to be an aspiration hazard.			
12. Ecological information	n			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			
Persistence and degradability	No data is available on the degradability of this product.			

Material name: Duster™

Bioaccumulative potential	No data available.		
Partition coefficient n-octa 1,1-difluoroethane	anol / water (log Kow) 0.75		
Mobility in soil	No data available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal considerati	ons		
Disposal of waste from residues / unused products	This product, as packaged, is a RCRA hazardous waste for flammability with a waste code of D001. The dispensed product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.		
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F		
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.		
14. Transport informatio	n		
DOT			
UN number UN proper shipping name	UN1030 1,1-Difluoroethane or Refrigerant gas R 152a		

UN number	UN1030
UN proper shipping name	1,1-Difluoroethane or Refrigerant gas R 152a
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	DOT-SP 11516: In accordance with this special permit, this product is not subject to labeling requirements unless offered for transportation by air. This product is not subject to placarding requirements. Outside packaging must be marked with proper shipping description and 'DOT-SP 11516'. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	T50, 11516
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	314, 315
ΙΑΤΑ	
UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
ERG Code	10L
Special precautions for user Other information	Read safety instructions, SDS and emergency procedures before handling.
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory informatio	n
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Not regulated. SARA 304 Emergency relea	Notification (40 CFR 707, Subpt. D) se notification
Not regulated. OSHA Specifically Regulate	d Substances (29 CFR 1910.1001-1050)
	Section 313 - Toxic Chemical: Listed substance
Not listed. CERCLA Hazardous Substa	nce List (40 CFR 302.4)
Not listed. CERCLA Hazardous Substa Not listed.	nces: Reportable quantity
Spills or releases resultin	g in the loss of any ingredient at or above its RQ require immediate notification to the National 24-8802) and to your Local Emergency Planning Committee.
Clean Air Act (CAA) Section	n 112 Hazardous Air Pollutants (HAPs) List
Not regulated. Clean Air Act (CAA) Section	n 112(r) Accidental Release Prevention (40 CFR 68.130)
1,1-difluoroethane (CAS	75-37-6)
Safe Drinking Water Act (SDWA)	Not regulated.
Food and Drug Administration (FDA)	Not regulated.
Superfund Amendments an Section 311/312 Hazard categories	d Reauthorization Act of 1986 (SARA) Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No
SARA 302 Extremely hazardous substance	No
US state regulations	
US. New Jersey Worker and	I Community Right-to-Know Act
1,1-difluoroethane (CAS US. Massachusetts RTK - S	·
•	75-37-6) nd Community Right-to-Know Law
Not listed. US. Rhode Island RTK	
Not listed.	_
US. California Proposition 6 California Safe Drinking V any chemicals currently li	Nater and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain isted as carcinogens or reproductive toxins.
Volatile organic compounds (VO EPA	
VOC content (40 CFR 51.100(s))	0 %
Consumer products (40 CFR 59, Subpt. C)	Not regulated
State	
Consumer products	This product is regulated as a Pressurized Gas Duster. This product is compliant for use in all 50 states.
VOC content (CA)	0 %
VOC content (OTC)	0 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	08-24-2017
Prepared by	Allison Yoon
Version #	01
Further information	CRC # 402/1002390
HMIS® ratings	Health: 1 Flammability: 4 Physical hazard: 1 Personal protection: B
NFPA ratings	Health: 1 Flammability: 4 Instability: 1
NFPA ratings	
Disclaimer	The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc
Revision Information	Product and Company Identification: Product Codes Composition/information on ingredients: Component information Fire-fighting measures: Suitable extinguishing media Handling and storage: Precautions for safe handling Physical & Chemical Properties: Multiple Properties Toxicological information: Ingestion Transport Information: Proper Shipping Name/Packing Group Regulatory Information: United States Other information, including date of preparation or last revision: Disclaimer Other information, including date of preparation or last revision: Further information GHS: Classification