




SAFETY DATA SHEET

1. Identification

Product identifier	Upside Down Marking Spray Paint - Caution Blue - 1 lb 1 oz
Other means of identification	
Product Code	No. 18202 (Item# 1005220)
Recommended use	Coating
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufactured or sold by:	
Company name	CRC Industries, Inc.
Address	885 Louis Dr. Warminster, PA 18974 US
Telephone	
General Information	215-674-4300
Technical Assistance	800-521-3168
Customer Service	800-272-4620
24-Hour Emergency (CHEMTREC)	800-424-9300 (US)
Website	www.crcindustries.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols Gases under pressure	Category 1 Liquefied gas
Health hazards	Carcinogenicity Specific target organ toxicity, single exposure Specific target organ toxicity, repeated exposure Aspiration hazard	Category 2 Category 3 respiratory tract irritation Category 2 Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard Hazardous to the aquatic environment, long-term hazard	Category 2 Category 2
OSHA defined hazards	Not classified.	
Label elements		

Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not apply while equipment is energized. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Do not breathe mist/vapors. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wear protective gloves/eye protection/face protection.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell. If exposed or concerned: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
water		7732-18-5	20 - 30
propane		74-98-6	15 - 25
solvent naphtha (petroleum), light aliph.		64742-89-8	15 - 25
calcium carbonate		1317-65-3	10 - 15
n-butane		106-97-8	10 - 15
distillates (petroleum), hydrotreated light		64742-47-8	1 - 5
titanium dioxide		13463-67-7	1 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Take off contaminated clothing and wash before reuse. Get medical attention if irritation develops and persists.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Ingestion	Call a physician or poison control center immediately. Clean mouth with water and drink afterwards plenty of water. Aspiration may cause pulmonary edema and pneumonitis. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Direct contact with eyes may cause temporary irritation. May cause respiratory irritation. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Carbon dioxide (CO2). Dry chemical powder. Water spray.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Collect spillage. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist/vapors. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices. For product usage instructions, see the product label.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	PEL	400 mg/m3	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
titanium dioxide (CAS 13463-67-7)	PEL	100 ppm 15 mg/m3	Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
n-butane (CAS 106-97-8)	STEL	1000 ppm
titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	100 mg/m3	
n-butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)	TWA	400 mg/m3	
		100 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear protective gloves such as: Silver Shield®. Nitrile.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	Blue.

Odor Aromatic.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range 95 °F (35 °C) estimated

Flash point -2.2 °F (-19.0 °C)

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 1.7 %

Flammability limit - upper (%) 10.9 %

Vapor pressure 3998.7 hPa estimated

Vapor density Not available.

Relative density 0.77 - 0.85

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 410 °F (210 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Percent volatile 93.7 % estimated

Other information

VOC-State Aerosol Coatings (MIR) 0.54

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. Contact with incompatible materials. Avoid freezing.

Incompatible materials Acids. Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May be fatal if swallowed and enters airways. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Direct contact with eyes may cause temporary irritation. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
Upside Down Marking Spray Paint - Caution Blue - 1 lb 1 oz		
Acute		
Dermal		
LD50	Rabbit	> 10000 mg/kg
Inhalation		
<i>Dust and mist.</i>		
LD50	Rat	> 6.82 mg/l, 4 hours
Oral		
LD50	Rat	> 20000 mg/kg

Components	Species	Test Results
distillates (petroleum), hydrotreated light (CAS 64742-47-8)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 5 mg/l, 4 hours
Oral		
LD50	Rat	> 5000 mg/kg

n-butane (CAS 106-97-8)

Acute

Inhalation

LC50 Rat 658 mg/l, 4 Hours

titanium dioxide (CAS 13463-67-7)

Acute

Dermal

LD50 Rabbit > 10000 mg/kg

Oral

LD50 Rat > 10000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Product	Species	Test Results
Upside Down Marking Spray Paint - Caution Blue - 1 lb 1 oz		
Aquatic		
<i>Acute</i>		
Crustacea	EC50	Daphnia
		9130.4346 mg/l, 48 hours
Fish	LC50	Fish
		15695.1016 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

n-butane	2.89
propane	2.36

Bioconcentration factor (BCF)

titanium dioxide	352
------------------	-----

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions If discarded, this product is considered a RCRA ignitable waste, D001. Empty container can be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.



14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	304
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity

Transport hazard class(es)**Class** 2.1**Subsidiary risk** -**Packing group** Not applicable.**ERG Code** 10L**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Other information****Passenger and cargo aircraft** Allowed with restrictions.**Cargo aircraft only** Allowed with restrictions.**IMDG****UN number** UN1950**UN proper shipping name** AEROSOLS, Limited Quantity**Transport hazard class(es)****Class** 2.1**Subsidiary risk** -**Packing group** Not applicable.**Environmental hazards****Marine pollutant** Yes, but exempt from the regulations.**EmS** F-D, S-U**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**DOT; IMDG****IATA**

15. Regulatory information
US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

Food and Drug Administration (FDA) Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)
Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

calcium carbonate (CAS 1317-65-3)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

calcium carbonate (CAS 1317-65-3)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

calcium carbonate (CAS 1317-65-3)

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

calcium carbonate (CAS 1317-65-3)

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-butane (CAS 106-97-8)

propane (CAS 74-98-6)

solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)

titanium dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including ethylbenzene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

carbon black (CAS 1333-86-4)

Listed: February 21, 2003

ethylbenzene (CAS 100-41-4)

Listed: June 11, 2004

titanium dioxide (CAS 13463-67-7)

Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated light (CAS 64742-47-8)

n-butane (CAS 106-97-8)
solvent naphtha (petroleum), light aliph. (CAS 64742-89-8)
titanium dioxide (CAS 13463-67-7)

Volatile organic compounds (VOC) regulations

EPA

Aerosol coatings (40 CFR 59, Subpt. E) Compliant

State

Aerosol coatings This product is regulated as a Ground Traffic and Marking Coating. This product is compliant for sale in all 50 states.

Maximum incremental reactivity (MIR) 0.54

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 02-17-2021

Prepared by Danica Fulmer

Version # 01

Disclaimer The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.