

## SAFETY DATA SHEET

### 1. Identification

Product identifier Nickel Anti-Seize & Lubricating Compound - 16 oz

Other means of identification

Product Code No. SL35913 (Item# 1007948)

Recommended use Anti-seize and lubricating compound

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone 24-Hour Emergency

800-424-9300 (US)

800-556-5074

(CHEMTREC)

Website crcindustries.com

## 2. Hazard(s) identification

Physical hazards Not classified.

**Health hazards** Sensitization, skin Category 1

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated

exposure.

Precautionary statement

**Prevention** Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to

ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe dust. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the

workplace. Wash thoroughly after handling. Wear protective gloves.

**Response** If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse. Get medical advice/attention if you feel unwell.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

### 3. Composition/information on ingredients

**Mixtures** 

No. SL35913 (Item# 1007948) Version #: 02 Revision date: 08-18-2023 Issue date: 08-19-2019

Chemical name	Common name and synonyms	CAS number	%
distillates (petroleum), solvent-refined heavy naphthenic		64741-96-4	60 - 70
graphite		7782-42-5	10 - 20
nickel		7440-02-0	5 - 15
aluminum		7429-90-5	1 - 5
amorphous silica		7631-86-9	1 - 5

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders. Seek medical attention and take along these instructions.

Immediately flush eves with plenty of water for at least 15 minutes. Get medical attention if Eve contact

irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions

Specific methods

General fire hazards

Carbon dioxide (CO2). Water Spray or Fog. Foam.

None known.

During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

Use standard firefighting procedures and consider the hazards of other involved materials. No unusual fire or explosion hazards noted.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up The product is immiscible with water and will sediment in water systems. Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Sweep up or vacuum up spillage and collect in suitable container for disposal. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

Precautions for safe handling

Do not breathe dust. Avoid contact with eyes, skin, and clothing. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities Store in a cool, dry place out of direct sunlight. Keep container tightly closed. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Components	Type	Value	Form
aluminum (CAS 7429-90-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
graphite (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
nickel (CAS 7440-02-0)	PEL	1 mg/m3	
US. OSHA Table Z-3 (29 CFR 1910. Components	1000) Type	Value	Form
aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Respirable fraction
/		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction
amorphous silica (CAS 7631-86-9)	TWA	5 mg/m3	Respirable fraction
7001 00 07		15 mg/m3	Total dust.
		0.8 mg/m3	
		20 mppcf	
graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	TWA	5 mg/m3	Inhalable fraction.
graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction
nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chem		Value	Form
Components	Type	Value	
aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Respirable.
		5 mg/m3	Welding fume or pyrophoric powder.
		10 mg/m3	Total
amorphous silica (CAS 7631-86-9)	TWA	6 mg/m3	
distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	2.5 mg/m3	Respirable.
graphite (CAS 7782-42-5)	IVVA	2.5 mg/ms	Respirable.

US. NIOSH: Pocket Guide to Chemical Hazards **Form** Components Value Type nickel (CAS 7440-02-0)

TWA

0.015 mg/m3

#### **Biological limit values**

Components	Value	Determinant	Specimen	Sampling Time	
nickel (CAS 7440-02-0)	5 μg/l	Nickel	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

**Exposure guidelines** Appropriate engineering

controls

Occupational Exposure Limits are not relevant to the current physical form of the product. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to

maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Nitrile. **Hand protection** Other Wear appropriate chemical resistant clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Wear a dust mask if dust is generated above exposure limits. Air monitoring is needed to determine actual employee exposure

levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

## 9. Physical and chemical properties

**Appearance** 

Solid. Physical state Paste. **Form** Silver. Color Mild. Odor

Not available. Odor threshold Not available.

Melting point/freezing point Initial boiling point and boiling

680 °F (360 °C) estimated

1220 °F (660 °C) estimated

range

Flash point

425.0 °F (218.3 °C) Cleveland Open Cup

**Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

Vapor pressure 330055.3 hPa estimated

Vapor density Not available.

1.18 Relative density

Solubility(ies)

Insoluble. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 500 °F (260 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

### 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Oxidizing material.

Hazardous decomposition

products

Carbon oxides. Metal oxides.

## 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** No adverse effects due to inhalation are expected.

**Skin contact** May cause an allergic skin reaction.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

aluminum (CAS 7429-90-5)

Acute Oral

LD50 Rat > 15900 mg/kg

amorphous silica (CAS 7631-86-9)

Acute Dermal

LD50 Rabbit > 6000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

distillates (petroleum), solvent-refined heavy naphthenic (CAS 64741-96-4)

<u>Acute</u> Dermal

LD50 Rabbit > 5000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

graphite (CAS 7782-42-5)

Acute Oral

LD50 Rat > 10000 mg/kg

nickel (CAS 7440-02-0)

**Acute** 

Dermal

LD50 Rat > 9000 mg/kg

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

amorphous silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

distillates (petroleum), solvent-refined heavy naphthenic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64741-96-4)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may

cause chronic effects.

12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability 
No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

However, it is the generator's responsibility to determine the proper classification and disposal

method at the time of disposal.

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### **CERCLA Hazardous Substance List (40 CFR 302.4)**

nickel (CAS 7440-02-0)

### **CERCLA Hazardous Substances: Reportable quantity**

nickel (CAS 7440-02-0)

100 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

### **Toxic Substances Control Act (TSCA)**

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

nickel (CAS 7440-02-0)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

**Food and Drug** 

Not regulated.

Administration (FDA)

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Respiratory or skin sensitization

categories Specific target organ toxicity (single or repeated exposure)

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

#### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
nickel	7440-02-0	5 - 15	

#### **US** state regulations

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Aluminum (CAS 7429-90-5)

Distillates (petroleum), solvent-refined heavy naphthenic; Baseoil - unspecified (CAS 64741-96-4)

### **US. New Jersey Worker and Community Right-to-Know Act**

ALUMINUM (CAS 7429-90-5)

GRAPHITE (NATURAL) (CAS 7782-42-5)

NICKEL (CAS 7440-02-0)

### **US. Massachusetts RTK - Substance List**

Aluminum (CAS 7429-90-5)

Graphite (natural) dust (CAS 7782-42-5)

Nickel (CAS 7440-02-0)

Oil mist (mineral) (CAS 64741-96-4)

Silica, amorphous (CAS 7631-86-9)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum (CAS 7429-90-5)

Graphite (CAS 7782-42-5)

Nickel (CAS 7440-02-0)

Silica (CAS 7631-86-9)

### **US. Rhode Island RTK**

ALUMINUM (DUST OR POWDER), METAL & OXIDE, WELDING FUMES, (CAS 7429-90-5)

GRAPHITE (NATURAL) (CAS 7782-42-5)

LUBRICATING OIL (MINERAL) (CAS 64741-96-4)

NICKEL CATALYST (FINELY DIVIDED, ACTIVATED, OR SPENT) (CAS 7440-02-0)

NUISANCE PARTICULATES (CAS 7631-86-9)

#### **California Proposition 65**



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

nickel (CAS 7440-02-0) Listed: October 1, 1989

California Proposition 65 - CRT: Listed date/Developmental toxin

nickel (soluble compounds) (CAS s~ni~d) Listed: October 26, 2018

California Proposition 65 - CRT: Listed date/Male reproductive toxin

nickel (soluble compounds) (CAS s~ni~d) Listed: October 26, 2018

### Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR 1.8 %

51.100(s))

Not regulated

Consumer products (40 CFR 59, Subpt. C)

State

Consumer products This product is regulated as an Anti-seize Lubricant (non-aerosol). This product is compliant for

use in all 50 states.

VOC content (CA) 1.8 % VOC content (OTC) 1.8 %

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Nο Japan Korea Existing Chemicals List (ECL) No New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

## 16. Other information, including date of preparation or last revision

Issue date08-19-2019Revision date08-18-2023Prepared byJoshua Weir

Version # 02

**Disclaimer**The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Material name: Nickel Anti-Seize & Lubricating Compound - 16 oz

No. SL35913 (Item# 1007948) Version #: 02 Revision date: 08-18-2023 Issue date: 08-19-2019

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### **Revision information**

Product and Company Identification: Product Codes

Hazard(s) identification: Prevention

Composition / Information on Ingredients: Ingredients

First-aid measures: Eye contact

Physical & Chemical Properties: Multiple Properties
Physical and chemical properties: Odor
Disposal considerations: Hazardous waste code
HazReg Data: North America

GHS: Classification