SAFETY DATA SHEET

1. Identification

Product identifier Cooling System Stop Leak - 15 fl oz

Other means of identification

No. 401214 (Item# 1008134) **Product Code**

Recommended use Engine block and cooling system repair

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

CRC Industries. Inc. Company name

885 Louis Dr. **Address**

Warminster, PA 18974 US

Telephone

General Information 215-674-4300 **Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Category 2A Health hazards Serious eye damage/eye irritation

> Carcinogenicity Category 2

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements





Signal word Warning

Hazard statement Causes serious eye irritation. Suspected of causing cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

> and understood. Use only outdoors or in a well-ventilated area. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after

Category 3

handling. Wear protective gloves/protective clothing/eye protection/face protection.

Response If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or

concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: Cooling System Stop Leak - 15 fl oz

No. 401214 (Item# 1008134) Version #: 01 Issue date: 04-30-2021

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	<u></u>
water		7732-18-5	80 - 90
sodium silicate		1344-09-8	5 - 10
cellulose		9004-34-6	1 - 3
Refractories, fibers, aluminosi	licate	142844-00-6	1 - 3
bentonite		1302-78-9	0.1 - 1
distillates (petroleum), solvent-dewaxed heavy parafl	inic	64742-65-0	0.1 - 1
copper		7440-50-8	≤ 0.1

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Rinse mouth. Get medical attention if symptoms occur. Ingestion

vision.

Most important

symptoms/effects, acute and

delayed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. medical attention and special

General information IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware

> Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

treatment needed

media

Specific hazards arising from

the chemical

and precautions for firefighters

Special protective equipment

Fire-fighting

equipment/instructions

Specific methods

No unusual fire or explosion hazards noted. General fire hazards

Move containers from fire area if you can do so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Prevent product from entering drains.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Material name: Cooling System Stop Leak - 15 fl oz

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Co Components	Туре	Value	Form
cellulose (CAS 9004-34-6)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	Form
cellulose (CAS 9004-34-6)	TWA	10 mg/m3	
copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Chemic	al Hazards		
Components	Туре	Value	Form
cellulose (CAS 9004-34-6)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Refractories, fibers, aluminosilicate (CAS 142844-00-6)	TWA	3 fibers/cm3	Fibrous dust.
•		3 fibers/cm3	Fiber.
		5 mg/m3	fibers, total dust

Biological limit values

No biological exposure limits noted for the ingredient(s).

SDS US

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear protective gloves such as: Neoprene. Nitrile.

Other Wear suitable protective clothing.

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

> NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Copper. Odor Mild.

Not available. Odor threshold

11.3 pН

Melting point/freezing point Not available.

Initial boiling point and boiling

211.9 °F (100 °C) estimated

range

Flash point None. **Evaporation rate** Slow.

Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

0.0007 hPa estimated Vapor pressure

Not available. Vapor density

Relative density 1.08

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

400 °F (204.4 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Viscosity Not available. 84.9 % estimated Percent volatile

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Material name: Cooling System Stop Leak - 15 fl oz

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Heat, flames and sparks. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Aldehydes. Alcohols. Ethers. Hydrocarbons. Ketones. Organic acids. Hydrogen. Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Based on available data, the classification criteria are not met.

Eye contact Causes serious eye irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

sodium silicate (CAS 1344-09-8)

Acute Oral Solid

LD50 Rat 1500 - 3200 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

distillates (petroleum), solvent-dewaxed heavy paraffinic 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-65-0)

Refractories, fibers, aluminosilicate (CAS 142844-00-6) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Material name: Cooling System Stop Leak - 15 fl oz

SDS US

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

> containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all

applicable regulations.

Not regulated. Hazardous waste code

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

CERCLA Hazardous Substance List (40 CFR 302.4)

copper (CAS 7440-50-8)

CERCLA Hazardous Substances: Reportable quantity

copper (CAS 7440-50-8) 5000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard Serious eye damage or eye irritation

Carcinogenicity categories SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

No. 401214 (Item# 1008134) Version #: 01 Issue date: 04-30-2021

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

cellulose (CAS 9004-34-6) copper (CAS 7440-50-8)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

US. Massachusetts RTK - Substance List

cellulose (CAS 9004-34-6) copper (CAS 7440-50-8)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

US. Pennsylvania Worker and Community Right-to-Know Law

cellulose (CAS 9004-34-6) copper (CAS 7440-50-8)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

US. Rhode Island RTK

cellulose (CAS 9004-34-6) copper (CAS 7440-50-8)

distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Refractories, fibers, aluminosilicate (CAS 142844-00-6)

California Proposition 65



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,4-dioxane (CAS 123-91-1) Listed: January 1, 1988 acetaldehyde (CAS 75-07-0) Listed: April 1, 1988 crystalline silica, tridymite (CAS 15468-32-3) Listed: October 1, 1988 ethylene oxide (CAS 75-21-8) Listed: July 1, 1987 quartz (CAS 14808-60-7) Listed: October 1, 1988

California Proposition 65 - CRT: Listed date/Developmental toxin

ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

California Proposition 65 - CRT: Listed date/Female reproductive toxin

ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

copper (CAS 7440-50-8)

distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

Volatile organic compounds (VOC) regulations

EPA

State

Europe

VOC content (40 CFR 0.1 %

51.100(s))

Consumer products

Not regulated

(40 CFR 59, Subpt. C)

Consumer products Not regulated

0.1 % VOC content (CA) VOC content (OTC) 0.1 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No

European List of Notified Chemical Substances (ELINCS)

No

Country(s) or region Inventory name On inventory (yes/no)*

JapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)No

New Zealand New Zealand Inventory No

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information, including date of preparation or last revision

Issue date 04-30-2021
Prepared by Allison Yoon

Version # 01

Further information CRC # 890A/1002872

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: Cooling System Stop Leak - 15 fl oz

No. 401214 (Item# 1008134) Version #: 01 Issue date: 04-30-2021 8 / 8